

TRACKER 2

Ultra-comfortable and technical, Tracker 2 provides protection from mechanical and chemical risks, making it unique in the safety glasses range.



1652001A • Clear Lens



1652002A • Smoke Lens



Accessories:

1652015 • Rx Adaptor



1652010A • Twilight Lens












50 g

- + 8 BASE CURVE, DISTORTION FREE LENS**
- + RUBBERISED EYE SEAL PROVIDES EXCEPTIONAL PROTECTION AGAINST DUST AND OTHER PARTICLES**
- + ADJUSTABLE HEAD STRAP**
- + CAN BE FITTED WITH AN RX PRESCRIPTION LENS**

bollé
SAFETY

TRACKER 2

MODEL	VERSIONS	PRODUCT CODE	LENS MARKING	FRAME MARKING	COATINGS
TRACKER 2	 Clear	1652001A	 +U6S	 Z87+ Z94	Anti-scratch/Anti-fog
	 Smoke	1652002A	 +U6S	 Z87+ Z94	Anti-scratch/Anti-fog
	 Twilight	1652010A	 +U6S	 Z87+ Z94	Anti-scratch/Anti-fog

LENS MARKING

Z87+ Impact rated for Plano product - tested and approved to ANSI Z87.1-2010, American National Standards Institute's Standard for Eye and Face Protection.

LENSES

- 2mm polycarbonate
- 8 base curve
- 99.99% UV 385 – Clear
- 99.99% UV 400 – Smoke and Twilight

APPLICATIONS

- Dust protection
- Engineering/process work
- Solar UV exposure
- Milling
- Rigging
- Laboratory work

MAIN MARKETS

- Mining
- Manufacturing
- Construction
- Local Government/Councils
- Utilities: power, gas and water boards
- Petro Chemical

FRAME MARKING

Z87+ Impact rated for Plano product - tested and approved to ANSI Z87.1-2010, American National Standards Institute's Standard for Eye and Face Protection.

ANSI guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc. Maximum protection for glasses. Use for high speed particles at extreme temperatures.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 8
FRAME	PC
TEMPLES	PC + TPR
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No



Non-contractual pictures

26/04/2020

Bollé Safety AU Pty Limited
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: sales@bollesafety.com.au

Hong Kong Bollé Safety
818, 8/F, Ocean Centre, Harbour City,
5 Canton Road, Tsim Sha Tsui,
Kowloon, Hong Kong
T.: +852 2732 5038

bolle-safety.hk

bolle
SAFETY