



Main

Range	Spacial
Accessory / separate part category	Busbar accessory
Product or component type	Busbar support
Anwendung	Multi-purpose Prisma application
Enclosure nominal dimensions	-
Mounting location	On structure of enclosure
Busbar position	Vertical
Range compatibility	Spacial SF Linergy LGYE Linergy BS Spacial SFP Prisma PH

Complementary

Cubicle-device connection	Linergy LGYE lateral busbar - fixed Linergy BS lateral busbar - fixed
Device composition	Fixing elements 1 metal support 2 insulating bar support
Quantity per set	Set of 1
Material	Bar support: plastic Metal support: steel
Fixing mode	By fixing element
Width	550 Mm fixing centers: 600 mm nominal:
Depth	39 mm
[In] rated current	3200 A

Packing Units

Package 1 Weight	1.76 kg
------------------	---------

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.