

## **FEATURES**

- Glass clear clarity for excellent visibility
- Excellent resistance to abrasion
- Suitable for food, water, chemicals, gas, fuel and oils
- EC compliant for food contact applications
- Highly resistant to a wide range of acids and alkalis
- Specially selected high tensile polyester fibres used at the optimum braid angle

# RS PRO PET, PVC Flexible Tubing, Transparent, 14mm External Diameter, 25m LongReinforced, 50mm Bend Radius,

RS Stock No.: 368-0205



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



**Product Description** 

An economical, light duty hose ideal for multi-purpose use and is especially popular for industrial air line equipment. It can also be used for food contact applications. Manufactured from transparent, low toxic PVC and reinforced with high tensile polyester fibres.

#### **General Specifications**

Material	PET,PVC
Colour	Transparent
Reinforced	Yes
Application	Compressed Air, Food, Water, shop floor airline applications Popular for pharmaceutical / scientific applications for the transfer of chemicals, For the transfer of food substances and liquids

#### **Mechanical Specifications**

Inner Diameter	10mm
Outer Diameter	14mm
Length	25m
Bend Radius	50mm
Safety Factor	3:1

#### **Operation Environment Specifications**

Minimum Operating Temperature	-15°C
Maximum Operating Temperature	+60°C
Maximum Working Pressure	10bar



### Approvals

**Compliance/Certifications** 

RoHS compliant / BS EN ISO 6224



Product Ref	Size I.D.	Size O.D.	Burst Pressure Bar	Bend Radius mm
VK06	6.3	11	30	30
VK08	8.0	12	30	40
PVK10	10.0	14	30	50
PVK12	12.5	18	30	60
PVK16	16.0	22	30	80
PVK19	19.0	25	30	95
PVK25	25.0	32	30	125
		+3%		
Maximum Minimum B	actor @23% working Pre Burst Pressu	ssure: re:	10 bar (147 30 bar (441	