

FEATURES

- Swivel castor
- Load capacity of 70kg
- Wheel diameter of 100 mm
- Overall height of 128mm
- Wheel width of 24mm
- Plate mounting type
- Fixing plate dimensions of 102mm x 84mm
- Fixing centres of 80mm x 60mm
- Rubber tyres
- Braked swivel rotation brake included
- Light duty
- Includes top plate fitting
- Four fixing holes of 8mm
- Roller hub bearings

RS PRO Braked Swivel Swivel Castor, 70kg Load Capacity, 100mm Wheel Diameter

RS Stock No.: 828-6306



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



Product Description

Move equipment quickly and safely around offices, warehouses or other environments with the help of these handy swivel castors from RS PRO. These general-purpose castors have a wheel diameter of 100 mm and can carry up to 70 kg.

The castors have a brake for safety and rubber tyres to protect your floor. Offering maximum mobility, they're able to rotate a full 360°. The wheels are fitted with roller hub bearings, which offer a higher load capacity than plain bore bearings.

General Specifications

| Rotation | Braked Swivel |
|----------------|--|
| Weight Class | Light Duty |
| Load Capacity | 70kg |
| Tyre Material | Rubber |
| Hub Material | Polypropylene |
| Includes Brake | Yes |
| Features | Top Plate Fitting, Ball bearing swivel head |
| Applications | General Purpose, offices, warehouses and other industrial environments |

Mechanical Specifications

| Mounting Type | Plate |
|------------------------|----------------|
| Wheel Diameter | 100mm |
| Wheel / Tread Width | 24mm |
| Overall Height | 128mm |
| Number of Fixing Holes | 4 |
| Fixing Hole Size | 8mm |
| Hub Bearing Type | Roller Bearing |



| Fixing Centres Specifications | | |
|-------------------------------|-------------|--|
| Fixing Centres | 80mm x 62mm | |
| Fixing Centres (Length) | 80mm | |
| Fixing Centres (Width) | 62mm | |

| Fixing Plate Specifications | | |
|-----------------------------|--------------|--|
| Fixing Plate Dimensions | 102mm x 84mm | |
| Fixing Plate Length | 102mm | |
| Fixing Plate Width | 84mm | |





Castor Wheels



| Specification | | |
|-------------------------|------------------------------|--|
| Application | General Purpose / Industrial | |
| Features | Ball Bearing Swivel Head | |
| Fixing Centres | 80x60mm | |
| Fixing Centres Length | 80mm | |
| Fixing Centres Width | 60mm | |
| Fixing Hole Size | 8mm | |
| Fixing Plate Dimensions | 102x84mm | |
| Fixing Plate Length | 102mm | |
| Fixing Plate Width | 84mm | |
| Hub Bearing Type | Roller | |
| Hub Material | Polypropylene | |
| Load Capacity | 70kg | |
| Number of Fixing Holes | 4 | |
| Overall Height | 128mm | |
| Rotation | Swivel & Brake | |
| Tyre Material | Grey Rubber Tyre | |
| Weight Class | Light Duty | |
| Wheel Diameter | 100mm | |
| Wheel Width | 24mm | |