



ENGLISH

Datasheet

Stock No: 185-7728

# RS Pro 3.6V Lithium Thionyl Chloride 1/2 AA Battery



## Product Details

### Single-memory Version

An electronic 5-digit LCD contact tachometer which also functions as a speed indicator (selectable).

Direct reading rpm

Surface speed ft/min. or m/min

Memory - recall of last reading, max., min

Requires 4 x AA alkaline cells (RS Stock No. [591-225](#))



|                    |                                |
|--------------------|--------------------------------|
| Measurement range  | 5 to 19999 rpm                 |
|                    | 0.05 to 1999.9 m/min.          |
|                    | 0.2 to 6560 ft/min.            |
| Resolution         | 0.1 rpm                        |
|                    | (1rpm above 1000rpm)           |
|                    | 0.01 m/min.                    |
|                    | (0.1m/min. above 100m/min.)    |
|                    | 0.1ft/min.                     |
|                    | (1ft/min. above 1000ft/min.)   |
| Accuracy           | $\pm(0.05\% +1 \text{ digit})$ |
| Overall dimensions | 170 x 72 x 37mm (H x W x D)    |

Contact

## Specifications

|                |              |
|----------------|--------------|
| Accessory Type | Cone & Wheel |
| For Use With   | Tachometer   |