





AP SEALER

ACRYLIC RESIN BASED WALL SEALER

Product Name	AP SEALER												
Product Description	A special Acrylic resin-based fast drying wall sealer with good penetration suitable for chalky surfaces and provides excellent adhesion of subsequent coats												
Designed Use	As a priming sealer for: <ul style="list-style-type: none"> • Concrete • Plaster • Brickwork • Hard and soft board 												
Performance	<ul style="list-style-type: none"> • Good adhesion to subsequent coats • Excellent alkaline and moisture sealing properties • Easy application • Good penetration and wetting onto substrates • Fast drying 												
Physical Properties	<p>Volume Solids 26%</p> <p>Theoretical Coverage* 12 – 15 m² / litre @ 25µm DFT</p> <p>Dry Film Thickness 25µm DFT</p> <p>Wet Film Thickness 96µm WFT</p> <p>Flash Point 32°C</p>												
Finishing	<p>Colours White only</p> <p>Finish Gloss</p> <p>Pack Size 5 & 20 liters</p>												
Practical Application	<p>Drying Times Surface Dry: 1 hour Recoat: 4 hours (overnight for the best results)</p> <p>Dilution 810-0560 Thinner</p> <p>Cleaning Up 810-0560 Thinner</p>												
Dilution Ratio	<p>Brush & Roller Ready for use</p> <p>Conventional Spray 0 – 5 %</p> <p>Airless Spray Ready for use</p>												
Surface Preparation	<p><u>Concrete Surfaces</u></p> <p>New unpainted surfaces & Repainting: Exterior check for fungus and algae growth. If present, treat the surfaces with fungicidal wash by brushing onto the surface with bleach mix (1 part household bleach with 3 parts water). Allow the mixture to penetrate the affected surface. Make good all defects with appropriate patching materials. When dry, remove all fungi, algae, chalk, loosely adhering contaminants by using high-pressure water-jetting.</p>												
Recommended Paint System	<p><u>Painted and Unpainted Surfaces: Concrete Surfaces & Walls</u></p> <table border="1"> <thead> <tr> <th colspan="2">1st coat</th> <th colspan="2">2nd coat</th> <th colspan="2">3rd coat</th> </tr> </thead> <tbody> <tr> <td>AP Sealer</td> <td>Recoat after 4 hours</td> <td>Super Unilic</td> <td>Recoat 2 hours</td> <td>Super Unilic</td> <td>Recoat 2 hours</td> </tr> </tbody> </table>	1 st coat		2 nd coat		3 rd coat		AP Sealer	Recoat after 4 hours	Super Unilic	Recoat 2 hours	Super Unilic	Recoat 2 hours
1 st coat		2 nd coat		3 rd coat									
AP Sealer	Recoat after 4 hours	Super Unilic	Recoat 2 hours	Super Unilic	Recoat 2 hours								

Storage	Store in cool dry place, avoid direct sunlight and keep away from naked flame and reach of children
Shelf Life	24 months under normal condition
Health & Safety	<p>This product contain solvent. Ensure adequate lighting and ventilation during application and drying. Do not use in confined spaces. Keep windows and doors open at all times.</p> <ul style="list-style-type: none">• This product does not contain added lead or mercury.• When applying paints, it is advisable to wear eye protection.• In case of contact with eyes, rinse immediately with plenty of water and see medical advice.• Use soap and water to remove splashes from skin.• Storage: Keep container closed and store in clean and dry conditions.• Do not empty into drains or water courses.• This product is flammable. Keep out of reach of children.• Safety Data Sheet (SDS) is available upon request. <div style="display: flex; justify-content: space-around; align-items: flex-end;"><div style="text-align: center;"> Keep seal tight</div><div style="text-align: center;"> Secure upright</div><div style="text-align: center;"> Wear proper protection</div><div style="text-align: center;"> Practice proper disposal</div></div>

For further information on Product Data, please contact:

Kansai Paint (Singapore) Pte Ltd
No.2 Tanjong Penjuru Singapore 609017
Tel.: +65 6264 0779 / Fax: +65 6267 0730 (Customer Service/ Supply Chain)
Website: www.kansaipaint.sg

*Practical coverage will vary according to the roughness and porosity of surface to be painted, the application method and condition, dry film and thickness and the skill of applicator.

The information in this technical data sheet is given to the best of our knowledge based on laboratory testing and practical experience and is provided as a general advice only. No guarantee of results is implied since the conditions of use are beyond our control. It is the responsibility of the users to ensure the suitability and proper usage of the product. We reserve the right to change the data without prior notice.