



### Main

|                           |               |
|---------------------------|---------------|
| Range                     | Kavacha       |
| Product or component type | Socket-outlet |
| Device short name         | AS            |
| Device application        | Power supply  |
| Colour tint               | White         |
| Colour tint (Frame)       | White         |

### Complementary

|                        |                  |
|------------------------|------------------|
| Wiring device mounting | Surface          |
| Rated current          | 13 A at 250 V AC |
| Number of gangs        | 1 gang           |
| Width                  | 80 mm            |
| Height                 | 117 mm           |
| Depth                  | 80 mm            |

### Environment

|                         |      |
|-------------------------|------|
| IP degree of protection | IP56 |
|-------------------------|------|

### Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 8.3 cm    |
| Package 1 Width              | 8.5 cm    |
| Package 1 Length             | 12 cm     |
| Package 1 Weight             | 272.727 g |
| Unit Type of Package 2       | CAR       |
| Number of Units in Package 2 | 45        |
| Package 2 Height             | 27.8 cm   |
| Package 2 Width              | 36 cm     |
| Package 2 Length             | 47 cm     |
| Package 2 Weight             | 12000 g   |
| Package 3 Height             | 130.0 cm  |

### Offer Sustainability

|                   |                     |
|-------------------|---------------------|
| EU RoHS Directive | Under investigation |
|-------------------|---------------------|