

FEATURES

 Rigid panel mounting socket retained in place by a nut, Which accepts 4mm diameter plugs. Is suitable for panels up to 13.5mm thick. Connection is via solder tag, although a solder bucket version is available.

RS PRO Banana Plugs & Connectors- 4mm Female Banana Connector Brown - Solder

RS Stock No.: 2121245



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Banana Plugs & Connectors



Product Description

Rigid panel mounting socket retained in place by a nut. Accepts 4mm diameter plugs. Is suitable for panels up to 13.5mm thick. Connection is via solder tag although a solder bucket version is available.

General Specifications

| Туре | Panel Mounting Socket |
|------------------|-----------------------|
| Colour | Brown |
| Gender | Female |
| Contact Material | Brass |
| Contact Plating | Silver Plated |

Electrical Specifications

| Voltage Rating | 250V ac |
|---------------------|---------------|
| Current Rating | 10A |
| Termination Method | Solder |
| Insulation Material | Polypropylene |

Mechanical Specifications

Length 28.5mm

Approvals

Declarations RoHS Certificate of Compliance

Similar Products

| Parameters | Stock# 423- 201 | Stock# 423- 239 | Stock# 103- 7637 | Stock# 454- 283 |
|---------------------|--------------------|--------------------|---------------------|--------------------|
| Brand | RS PRO | RS PRO | RS PRO | RS PRO |
| Colour | Black | Red | Red | Black |
| Gender | Female | Female | Male | Male |
| Contact Material | Brass | Brass | Stainless Steel | Brass |
| Voltage Rating | 50V dc | 50V dc | 50V | 1kV |
| Current Rating | 16A | 16A | 30A | 30A |
| Termination Method | Solder | Solder | Solder | Solder |
| Insulation Material | POM | POM | | PP |

Banana Plugs & Connectors



| Length | 52.9mm | 52.9mm | | |
|-------------------------|-----------------|-----------------|-----------------|--|
| Height Above Panel | 24mm to 32mm | 24mm to 32mm | 24mm to 32mm | |
| Overall Diameter | 14mm | 14mm | 14mm | |
| Thread Size | 4BA clearance | 4BA clearance | | |
| Maximum Panel Thickness | 12.7mm | | | |

Product Dimensions Details

Dimensions

