

APDU9953

APC Rack PDU 9000 Switched, ZeroU, 32A, 230V, (21) C13 & (3) C19



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Colour	Black
PDU type	Switched
Cable length	3.05 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets Safety guide

Complementary

Main Input Voltage	200 V 208 V 230 V
Height	182.9 cm
Width	5.6 cm
Depth	4.6 cm
Net weight	7.34 kg
Mounting location	Side
Mounting preference	No preference
Input Connection Type	IEC 60309 32 A 2P + E
Mounting mode	Not rack-mountable
Number of rack unit	0U
USB compatible	No
Mounting position	Vertical
Communication port protocol	SNMP Redfish
Permissible voltage	220...240 V
Max line current	32 A
Input current limits	32 A
Load capacity	7400 VA
Network frequency	50/60 Hz
Number of power socket outlets	21 IEC 60320 C13 3 IEC 60320 C19
Communication network type	10/100/1000BASE-T

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.






Environment

Product certifications	VDE[RETURN]EAC[RETURN]RCM
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3
Ambient air temperature for operation	-5...60 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	204 cm
Package 1 Width	12.4 cm
Package 1 Length	16.5 cm
Package 1 Weight	9.95 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------