## APCRBC132



★★★★★ 5.0 (1) Write a review

Genuine APC RBC(TM) are tested and certified for compatibility to restore UPS performance to the original specifications.

RoHS

Includes: All required connectors, Battery recycling guide, Installation guide, Metallic battery tray or enclosure, Reusable packaging

## **Technical Specifications**

Input	
Number of Power Cords	1
Batteries & Runtime	
Battery type	Lead-acid battery
Battery mounting	Enclosed battery cartridge
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Physical	
Maximum Height	3.27inches (83MM, 8.3CM)
Maximum Width	8.5inches (216MM, 21.6CM)
Maximum Depth	13.5inches (343MM, 34.3CM)
Net Weight	22.05lbs. (10.0KG)
Shipping weight	24.05lbs. (10.91KG)
Shipping Height	5.98inches (152MM, 15.2CM)
Shipping Width	14.49inches (368MM, 36.8CM)
Shipping Depth	19.49inches (495MM, 49.5CM)
Color	Black
Units per Pallet	20.0
Environmental	
Operating Temperature	32 - 113 °F (0 - 45 °C)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 10000ft (0 - 3048meters)

Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 50000ft (0 - 15240meters)
Δ <del>Σ</del> C	$\circ \succeq \equiv$
Comormance	
Standard warranty	2 years repair or replace
Sustainable Offer Status	
RoHS	Compliant
Proposition 65 Warning	Available in Documentation tab
SIGN UP FOR EMAIL	
I'd like to receive news and commercial info from Schneider El Policy.	ectric and its affiliates via electronic communication means such as email. For more details, please read our Privacy
Email	

I am a...

OK

 $\sim$ 

Go

WHO WE ARE	CONNECT WITH US
About APC	Press
Investor Relations	APC Blog
Careers	Schneider Electric Data Center Blog
Sustainability	Contact Us

## FIND A RESELLER

Zip/Postal Code	Find
-----------------	------

## CATALOG KEYCODE

Enter Key Code



Terms & Conditions

Data Privacy and Cookie Policy

Change your cookie settings

©2021, Schneider Electric