

# Datasheet

## Conquer 6.3 x 32 mm T Cartridge Fuse, 0.25 A, 250 V ac

RS Stock Number: 668-6060

6.3Ø x 32 mm Time-Lag Fuse



### Electrical Characteristics

Ampere Rating	Opening Time			
	1 In	1.35 In	2 In	
	MIN	MAX	MIN	MAX
200mA - 3A	4 hr	1 hr	5 sec	120 sec
3.15A - 30A	4 hr	1 hr	12 sec	120 sec
Above 30A	4 hr	1 hr	12 sec	-

### Interrupting Rating

200mA - 10A:	10,000 amperes at 125V AC
200mA - 1A:	35 amperes at 250V AC
1.2A - 3.5A:	100 amperes at 250V AC
3.75A - 30A:	200 amperes at 250V AC
10.1A - 30A:	1,000 amperes at 32V AC

### Product Characteristics

Operating Temperature	-55 °C to 125 °C
Material	Body: Glass / Caps: Nickel Plated Brass
Leads Wire	Ø0.8 mm 12A and less. Ø1.0 mm for rating above 13A to 19A. Ø1.2 mm for rating above 20A.

### Packaging

Packaging Option	Quantity
Bulk	ADL: 500 pcs / box ADP-A: 250 pcs / box

### Mechanical Dimensions (mm)

