




Overview

Lead time	Usually in Stock
-----------	------------------



Main

Colour	Black
PDU type	Basic
Cable length	1.98 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets Toolless mounting kit

Complementary

Main Input Voltage	120 V 200 V 208 V 230 V 240 V
Height	61 cm
Width	4.4 cm
Main Output Voltage	208 V 230 V
Depth	4.4 cm
Net weight	2 kg
Mounting location	Side
Mounting preference	No preference
Input Connection Type	IEC 60320 C14
Mounting mode	Rack-mounted
Number of rack unit	0U
Mounting position	Vertical
Permissible voltage	100...240 V
Input current limits	10 A
Load capacity	2300 VA
Network frequency	50/60 Hz
Number of power socket outlets	15 IEC 60320 C13

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Product certifications	cUL listed[RETURN]CE[RETURN]GOST[RETURN]Queensland Australia[RETURN]UL listed[RETURN]VDE
Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	64.8 cm
Package 1 Width	17.8 cm
Package 1 Length	15.2 cm
Package 1 Weight	2.724 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------