

FEATURES

- High quality nylon tyre
- Swivel castors
- Non-slip rubber feet
- Vibration damping rubber feet

RS PRO Swivel Swivel Castor, 1000kg Load Capacity, 75mm Wheel Diameter

RS Stock No.: 611-4442



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



Product Description

RS PRO castors are a range of multifunction levelling castors. These wheels are versatile and are an ideal choice for equipment that needs to be mobile, but when in place is completely firm and stationary. They can be used in numerous applications such as Vending machines, Medical appliances and Workstations. The plate is steel with a khaki powder coating whilst the bracket is aluminium die-casting, also featuring bi-level balls upon balls for full swivel.

General Specifications

| Rotation | Swivel |
|----------------------|---|
| Weight Class | Heavy Duty |
| Load Capacity | 1000kg /1pcs |
| Load Capacity / 4pcs | 2000kg |
| Tyre Material | Nylon |
| Hub Material | Nylon |
| Includes Brake | No |
| Features | Corrosion Resistant, Impact Resistant, Shock Absorbing |
| Applications | Vending machines, Medical appliances, Workstations, Measuring Instruments |

Mechanical Specifications

| Mounting Type | Plate |
|------------------------|--------------|
| Wheel Diameter | 75mm |
| Wheel / Tread Width | 30mm |
| Overall Height | 120mm |
| Number of Fixing Holes | 4 |
| Fixing Hole Size | 11mm |
| Hub Bearing Type | Ball Bearing |
| Levelling Extent | 12mm |
| Offset | 52mm |



| Fixing Centres Specifications | | |
|-------------------------------|-------------|--|
| Fixing Centres | 95mm x 95mm | |
| Fixing Centres (Length) | 95mm | |
| Fixing Centres (Width) | 95mm | |

| Fixing Plate Specifications | | |
|-----------------------------|-------------|--|
| Fixing Plate Dimensions | 70mm x 70mm | |
| Fixing Plate Length | 70mm | |
| Fixing Plate Width | 70mm | |

Operation Environment Specifications

| Operating Temperature | -10°C to 90°C |
|-----------------------|---------------|
|-----------------------|---------------|





Castor Wheels





Technical Data

| Wheel Diameter | 75 mm |
|----------------------|-------------|
| Width of Tread | 30 mm |
| Hardness of Tread | 70 Shore D |
| Size of Plate | 95 x 95 mm |
| Plate Hole Centers | 70 x 70 mm |
| Plate Hole | 11 mm |
| Leveling Extent | 12 mm |
| Offset | 52 mm |
| Overall Height | 120 mm |
| Temperature | -10 ~ +90°C |
| Load Capacity / 1pcs | 1,000 kg |
| Load Capacity / 4pcs | 2,000 kg |



