

8.4" Resistive IP66 Water-proof Touch Monitor (High Brightness)

Products application :

- POS Terminal
- Industrial PC
- Kiosk
- Gaming
- Medical apparatus
- Personal computer
- Mobile GPS
- Office automation
- Security system of the house
- Car-mounted amusement
- Military equipment
- Communicate



AIM-PM5RIP66084-R07_HB1K

Order information :

Touch interface :

Mount type :

AIM-PM5RIP66084-R07_HB1K	USB	Panel Mount.
AIM-PM5RIP66084-R08_HB1K	RS232	



8.4" Resistive IP66 Water-proof Touch Monitor (High Brightness)

Display Specifications :

Active Area	170.4 × 127.8 mm
Pixel Pitch	0.1665 × 0.1665 mm
Brightness	1000 cd/m ²
Contrast Ratio	1000 : 1
Resolution	1024 × 768 (XGA)
Viewing Angle	L/R 176° ; U/D 176°
Response Time	25 ms (Tr + Tf)
Display Colors	16.7 Million
Display Modes	640×480 ; 800×600 ; 1024×768
Signal input	VGA ; Audio ; DVI ; HDMI
Speaker	1W (8Ω) × 1
OSD Keyboard	⊕Power ⊕Auto adjust ⊕+ ⊕- ⊕Menu
Power Source	DC 12V (DC Jack Φ2.1mm)
Power Consumption	≤18w
Storage 、 Operation	-40~90°C ; -30~80°C
VESA	75×75 ; 100×100 mm
Casing Colors	Black (OEM other colors)



AIM-PM5RIP66084-R07_HB1K

Accessory VGA cable / HDMI cable / Audio cable / AC100~240V Adapter / Power cable / USB or RS232 cable / Touch pen / Cleaning wipes / Driver Disk

※DVI cable (Optional)

※AiM Touch has the right to update specs without further notice



8.4" Resistive IP66 Water-proof Touch Monitor (High Brightness)

Touch Feature :

Input Method	Finger, gloved hand, or stylus activation
Activation Force	≤50g
Linearity	≤1.5%
Surface	≥3H
Life Time	≥35,000,000
Application	Writing and Signature Capture Capability

Software Feature :

Calibration	Fast full oriental 4 points position
Compensation	Edge compensation. Accuracy 25 points linearity compensation
Draw Test	Position and linearity verification
Controller	Support multiple controllers
Languages	English · Simple Chinese · Traditional Chinese · Japanese · French · German · Spanish · Korean · Arabic · Czech · Danish · Dutch · Greek · Hungarian · Italian · Norwegian · Russian · Polish · Portuguese · Slovenian · Swedish · Thai · Turkish
Mouse Emulator	Right / left button emulation. Auto Right / left Click (PDA function)
Touch Style	Drawing a Mode · button a Mode · Touch Off/ on Switch
Double Click	Configurable double click speed · Configurable double click area
Sound Modes	No sound · Touch down · Touch up
COM Port Support	COM1 ~ COM255 for Windows and Linux COM1 ~ COM8 for MS- DOS
Display Support	display rotation · Support multiple monitors
Support O.S	All Windows-32/64bit O.S Android ; Linux ; MAC



AIM-PM5RIP66084-R07_HB1K

3 Year Warranty
LCD Panel 1 Year