

NSYPLA553G

Floor standing enclosure polyester vers.PLA
completely sealed 500x500x320 IP65



Main

Range	Thalassa
Product name	Thalassa PLA
Device application	Multi-purpose
Product or component type	Suitable enclosure
Device short name	PLA
Enclosure nominal height	500 mm
Enclosure nominal width	500 mm
Enclosure nominal depth	320 mm
Enclosure mounting	Floor-standing
Device composition	1 door 1 rear panel 2 side part 1 top part 1 bottom part

Complementary

Body type	Sealed top and bottom part assembled with side parts
Door type	Plain front
Number of doors	1
Door opening	Reversible 120 °
Lock type	2 points lock, 5 mm double-bar
Accessibility for operation	Front Rear
Removable parts	Door by hinges Rear panel by fixing element
Material	Polyester reinforced with fibreglass
Colour	Grey RAL 7035
Standards	IEC 62208 UL 508 A
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3R NEMA 4/4X NEMA 3S NEMA 3X NEMA 5
Product certifications	UL/cUL listed Veritas DNV Marine

Environment

IP degree of protection	IP65 completely sealed IEC 60529
IK degree of protection	IK10 plain door IEC 62262
fire resistance	960 °C IEC 62208
ambient air temperature for storage	-35...90 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1511 - Schneider Electric declaration of conformity

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

Warranty period	18 months
-----------------	-----------
