

**ENGLISH** 

# **Datasheet**

# **Heating Element Drum Heater - Silicone 900mm**

RS Stock number 790-4889

## Standard Drum heaters sizes

Silicone drum heaters are used to reduce the viscosity of liquids, a maximum of 3 can be applied to 200 litre drums to either speed up the melting process or for even heat distribution, class II double insulated.

Other sizes and specifications can also be easily made.

#### Standard drum Sizes

| Litres | Dimensions   | Wattage | Voltage | Temp Control C | Weight kg |
|--------|--------------|---------|---------|----------------|-----------|
| 200    | 250 x 1740mm | 2000    | 110/230 | 30 - 150       | 0.5       |
| 200    | 125 x 1740mm | 1500    | 110/230 | 30 - 150       | 0.3       |
| 20     | 200 x 860mm  | 800     | 110/230 | 30 - 150       | 0.4       |
| 18     | 250 x 900mm  | 1000    | 110/230 | 30 - 150       | 0.5       |



#### Materials for drum heating

- Adhesives (e.g. Hot melt)
- Asphalt/tar/creosote
- Brine
- Chemicals
- Chocolate
- Corn syrupFat/grease/lard
- · Finish pretreatment formulations
- Fuel oils
- Glycerin
- · Glycol (ethylene, propylene)
- Honey
- · Liquid sugar/dextrose/sucrose
- Lubricating oils
- Mastics
- Mineral oil
- Molasses
- · Materials vulnerable to freeze damage
- Paints
- Plastics
- Resins (e.g. Polyurethane foam components)
- · Solvents (nonflammable)
- Vegetable oils
- Wax

NOTE: Excessive heat may be harmful to some materials.

### Applications

- · PREHEATING OF PROCESS INGREDIENTS
- · MELTING SOLIDIFIED MATERIAL
- CONTROLLING VISCOSITY
- · PROMOTING DISSOLUTION
- SPEEDING LIQUID FLOW
- REDUCING RESIDUE IN DRUM
- · SPEEDING CHEMICAL ACTION
- PROTECTING AGAINST FREEZING