



# MASTER LEDspot LV AR111

## MAS LED ExpertColor 15-75W 930 AR111 24D

Delivering a warm, halogen-like accent beam, MASTER LEDspot LV AR111 is an ideal retrofit solution for spot and general lighting applications in the hospitality and retail industry. It is particularly suitable for general lighting where the light is on all the time, such as creative accent lighting applications in shops, restaurants, hotels, and especially for galleries, exhibitions and museums. The robustly designed MASTER LEDspot LV AR111 offers various beam angles for a clearly defined beam spread. There is no UV or IR in the beam, making it suitable for illuminating heat-sensitive objects (food, organic materials, paintings, etc.). The patented intelligent driver enables broad compatibility with existing electromagnetic and electronic halogen transformers. MASTER LEDspot LV AR111 delivers huge energy savings and minimises maintenance cost without any reduction in brightness.

#### **Product data**

General Information	
Cap-Base	G53 [G53]
Nominal lifetime	40,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes
Light Technical	
Color Code	930 [CCT of 3000K]
Beam Angle (Nom)	24 degree(s)
Luminous Flux	1,000 lm
Luminous Intensity (Nom)	3,500 cd
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
	· · · · · · · · · · · · · · · · · · ·

Luminous Efficacy (rated) (Nom)	66.00 lm/W
Color Consistency	<4
Color rendering index (CRI)	97
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	- Hz
Input Frequency	- Hz
Power Consumption	15 W
Lamp Current (Nom)	1,800 mA
Wattage Equivalent	75 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.7


Datasheet, 2023, April 16 data subject to change

## **MASTER LEDspot LV AR111**

Voltage (Nom)	ac electronic 12 V	
Temperature		
T-Case Maximum (Nom)	74 °C	
Controls and Dimming		
Dimmable	Yes	
Mechanical and Housing		
Bulb Shape	AR111	
Approval and Application		
Suitable For Accent Lighting	Yes	
Energy Consumption kWh/1000 h	17 kWh	


Product Data		
Order product name	MAS LED ExpertColor 15-75W 930 AR111 24D	
Full product name	MAS LED ExpertColor 15-75W 930 AR111 24E	
Full product code	871869969093900	
Order code	929002239108	
Material Nr. (12NC)	929002239108	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	8718699690939	
Numerator - Packs per outer box	6	
EAN/UPC - Case	8718699690946	

## Dimensional drawing




Product	D	С
MAS LED ExpertColor 15-75W 930 AR111 24D	111 mm	62 mm

### Photometric data








General uniform lighting - MAS LED ExpertColor 15-75W 930 AR111 24D


## **MASTER LEDspot LV AR111**


#### Photometric data



Spectral Power Distribution Colour - MAS LED ExpertColor 15-75W 930 AR111 24D

#### Lifetime





Life Expectancy Diagram - MAS LED ExpertColor 15-75W 930 AR111 24D

Lumen Maintenance Diagram - MAS LED ExpertColor 15-75W 930 AR111 24D



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.