

Copper Paste



Protecting, separating and lubricating agent for highly stressed parts in high-temperature applications

Copper Paste is corrosion resistant and strong. It contains no sulphur, lead or nickel.

WEICON Copper Paste is used as an assembly lubricant for all kinds of threaded joints and sliding surfaces. It forms an effective lubricating and separating film which protects the functional surfaces on plug-in tools, wear bushings, screws, and all kinds of threaded, plug-in and bayonet joints against corrosion and seizing.

It can be used to reduce vibration on brake blocks and guides, brake cams and pins, car and truck battery terminals and other electrical connections, wheel bolts and nuts, and on wear bushings at electrical, compressed air and hydraulic hammers. The product can be used in many industrial applications.

Technical Data

Basic Oil	mineral oil
Colour	copper
Consistency assignment (DIN 51818)	NLGI-Class 1
Thickener	aluminium complex soap
density	1,1 g/cm ³
Solid lubricant	copper / graphite
Coefficient of friction	0,11 - 0,13
Friction total	0,12 μ
Friction thread	0,11 μ
Friction head bottom	0,13 μ
VKA-TEST (DIN 51350) welding load	3.200 N

Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

Kinematic viscosity basic oil (+40°C DIN 51562)	180 mm ² /s
Drop Point (IP 396)	+180 °C
Worked penetration (DIN ISO 2137)	310 - 340 1/10 mm
Temperature resistance	-20 to 1.100 °C

Surface pre-treatment

Depending on the degree of soiling, clean and degrease surfaces with WEICON Cleaner S first. Used threads should be cleaned with a wire brush and WEICON Cleaner S.

Processing

Apply a good quantity of Assembly Paste with a brush, cloth or plastic sponge.

Processing press pack

Remove original closure. Regulate discharge by smooth turning of the cap from min. to max. Press the lever and process the medium. After having turned the cap into the "min." position the valve closes automatically and the product flow is stopped.

On threads it is important that Assembly Paste is applied down to the thread root to ensure a good sealing effect. Assembly Paste must not be mixed

Safety and health

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes:

26200003	Copper Paste 30 g
26200012	Copper Paste 120 g
26200040	Copper Paste 400 g
26200045	Copper Paste 450 g
26200050	Copper Paste 500 g
26200085	Copper Paste 85 g
26200100	Copper Paste 1.0 kg
26200200	Copper Paste 200 ml
26200910	Copper Paste 10.0 kg

Accessories:

10953001	Processing Spatula, short
10953003	Processing Spatula, long
11202500	Cleaner Spray S, 500 ml
11850200	Hand Protective Foam, 200 ml

WEICON GmbH & Co. KG
(Headquarters)
Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca
www.weicon.ca

WEICON Kimya Sanayi Tic. Ltd. Şti.
Turkey
phone +90 (0) 212 465 33 65
info@weicon.com.tr
www.weicon.com.tr

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON South East Asia Pte Ltd
Singapore
phone (+65) 6710 7671
info@weicon.com.sg

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weiconcz.cz

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es