

Datasheet  
**Stock No:1706992**

# RS Pro

## N STRAIGHT BULKHEAD FLANGE MOUNT JACK - JACK ADAPTER

APPROVED by \_\_\_\_\_ DATE: \_\_\_\_\_

DESCRIPTION		N STRAIGHT BULKHEAD FLANGE MOUNT JACK-JACK ADAPTER	
DRAWN	TOLERANCE	品名	40611206100003
Jackie	X ±0.2	日期	01.04.18
CHECK	XX ±0.1	标题	NRHS COMPLIANT (500)
Arc	XXX ±0.05	UNIT	DWG.NO. 61-0023-Z
APPROVAL	ANGLE ±5°	位	mm<math>(in)</math>
Jenny	例 4:1	SCALE	

**1.0 ELECTRICAL**

1.1 FREQUENCY RANGE: DC-11 GHz  
 1.2 NOMINAL IMPEDANCE: 50 OHM  
 1.3 VOLTAGE RATING: 1000 VOLTS MAX.  
 1.4 VSWR: 1.1 MAX. @6 GHz  
 1.3 MAX. @11 GHz

**2.0 MATERIALS**

2.1 BODIES: BRASS PER JIS-C3604  
 2.2 CENTER CONTACT: BERYLLIUM COPPER PER ASTM B196 UNS C17300  
 2.3 INSULATION: TEFLON PER ASTM D1457 AND ASTM D1710

**3.0 FINISHES AND OTHERS**

3.1 SEE BELOW TABLE FOR DETAILS.

**4.0 MECHANICAL**

4.1 INTERFACE IN ACCORDANCE WITH: MIL-STD-348A

**5.0 ENVIRONMENTAL**

5.1 OPERATING TEMPERATURE RANGE: -65° C TO +165° C

NO	DESCRIPTION	MATERIAL	Q'TY	FINISH
7	NUT	BRASS	1	WHITE BRONZE 80 μ" MIN.
6	WASHER	BRASS	1	WHITE BRONZE 80 μ" MIN.
5	O-RING	SILICONE	1	BLACK
4	INSULATION	TEFLON	1	NONE
3	BODY	BRASS	1	WHITE BRONZE 80 μ" MIN.
2	CHASSIS	BRASS	1	WHITE BRONZE 80 μ" MIN.
1	CENTER CONTACT	BERYLLIUM COPPER	1	GOLD 3 μ" MIN.