



Overview

Lead time	Usually in Stock
-----------	------------------



Main

Colour	Black
PDU type	Switched
Cable length	3.05 m
Number of cables	1
Provided equipment	Documentation CD Installation guide Rack mounting brackets

Complementary

Main Input Voltage	200 V 208 V 230 V
Height	8.9 cm
Width	44.5 cm
Main Output Voltage	230 V
Depth	11.4 cm
Net weight	4.5 kg
Mounting location	Front Rear
Mounting preference	No preference
Input Connection Type	IEC 60309 32 A 2P + E
Mounting mode	Rack-mounted
Number of rack unit	2U
Mounting position	Horizontal
Permissible voltage	220...240 V
Input current limits	32 A
Load capacity	7360 VA
Network frequency	50/60 Hz
Number of power socket outlets	16 IEC 60320 C13

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Product certifications	CE[RETURN]GOST[RETURN]IRAM[RETURN]MIC[RETURN]VDE
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3
Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14 cm
Package 1 Width	36.8 cm
Package 1 Length	50.8 cm
Package 1 Weight	6.55 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------