

ABS box IP66 IK07 RAL7035 Int.H225W175D80 Ext.H241W194D194 Opaque cover H20

NSYTBS24198

Range	Thalassa			
Product name	Thalassa TBS			
Device application	Multi-purpose			
Category	Industrial box			
Height	241 mm			
Width	194 mm			
Depth	87 mm			
Internal height	225 mm			
Internal width	175 mm			
Internal depth	80 mm			
Enclosure mounting	Wall mounted			
Device composition	1 body 1 cover 4 cover screw			
Body type	One piece moulded			
Type of front cover	Low plain cover			
Cover fixing	Plastic screws			
Lock type	Captive screw flat outside sealed area			
Removable parts	Cover by captive screws			

Complementary

Material	ABS (acrylonitrile butadiene-styrene)			
Colour	Grey (RAL 7035)			
Standards	IEC 62208			
Product certifications	TÜV			
Electrical insulation class	Class II			
IP degree of protection	IP66 conforming to NEMA 4.4X			
IK degree of protection	IK07 conforming to IEC 62262			
Glow wire resistance	650 °C conforming to IEC 60695-2-11			

Operating temperature -2560 °C	
Net weight 0.622 kg	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	618.0 g
Package 1 Height	10.0 cm
Package 1 width	20.0 cm
Package 1 Length	25.5 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	12
Package 2 Weight	8.362 kg
Package 2 Height	40.0 cm
Package 2 width	40.5 cm
Package 2 Length	61.0 cm
Unit Type of Package 3	PAM
Number of Units in Package 3	300
Package 3 Weight	222.0 kg
Package 3 Height	214.0 cm
Package 3 width	100.0 cm
Package 3 Length	120.0 cm

Offer Sustainability

Sustainable offer status	Green Premium product			
REACh Regulation	REACh Declaration			
REACh free of SVHC	Yes			
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration			
Toxic heavy metal free	Yes			
Mercury free	Yes			
RoHS exemption information	Yes			
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)			
Environmental Disclosure	ronmental Disclosure Product Environmental Profile			

Contractual warranty

Warranty	18 months		
----------	-----------	--	--