



ENGLISH

Datasheet

Stock No: 519-481

RS Pro Steel Grey Modular Shelving Shelf x 400mm



Image representative of range

Product Details

Shelf Kit

Additional shelf kit to fit Modular Shelving systems

Caution

The maximum safe working load per shelf is 160kg, to be uniformly distributed in both directions, maximum load per bay 1200kg.

Also: All runs of shelving require bracing. This must be in the form of a rear cross-brace assembly or a rear cladding kit and must be fitted at least one bay in six.



Modular Shelving

The RS modular shelving system has been designed as an integrated system in which each part slots together into standard modules. The shelf design incorporates a built-in box beam concept which creates inherent strength and rigidity as well as simplifying installation. A versatile system which is quick, easy and simple to erect or modify, with no nut and bolt assembly of the shelving. The uprights are perforated at 50 mm intervals to accept shelves that clip lock together with special shelf locking clips which have a wedging action when loaded, the greater the load, the stronger the structure. All major components are manufactured from steel with 'graphite' grey uprights and light (RAL7035) grey shelves and cladding paint finish. Available in open bay or clad bay versions, height 2.1 m, width 1 m, with a selection of shelf depths and accessories.

Contents			
	Starter bay qty	Extension bay qty	Shelf kit qty
Frame	2	1	
End cap	4	2	
Feet	4	2	
Cross brace	1 (open bay only)		
Shelves	4	4	2
Shelf clips	16	16	8

Specifications:

System	Modular Shelving
Component Type	Shelf
Load Capacity	160 kg, 1200 kg
Depth	400mm
Material	Steel
Colour	Grey