

ENGLISH

Datasheet

RS PRO Cable Clip 10.1mm Black PE

RS Stock No: 184-4609



Product Details

RS Pro cable clip in black colour, has a maximum bundle diameter of $10.1 \, \text{mm}$. The cable cleat is manufactured from low density polyethylene, which has high strength and impact resistance. The material is resistant to corrosion and UV light. It is stable at temperature of $-30 \, \text{to} +60 \, ^{\circ}\text{C}$.

Features and Benefits

- Comes in black colour
- Low density polyethylene (LDPE) construction
- Temperature range from -30 to +60°C






Specifications:

Affixing Method	Screw
Cable Clip/Clamp Style	Cable Clip
Colour	Black
Material	PE
Maximum Bundle Diameter	10.1 mm

MS4 = RS 184-4609 MS5 = RS 184-5214 MS6 = RS 184-4615 MS7 = RS 184-5220 MS8 = RS 184-4621 MS9 = RS 184-4637 MS10 = RS 184-4643



Dimensional Data

Reference Numbers	Dimensions						
Standard Polypropylene	Width	Height	Fixing Centres	Clearance Bolt			
, олургоруголго	Α	В	С	Holes			
	mm	mm	mm	mm			
Single Fixing							
MS 5	17.5	28.0	N/A	6			
MS 6	20.0	31.0	N/A	6			
MS 7	23.0	34.0	N/A	6			
MS 8	25.0	38.0	N/A	6			
MS 9	28.5	41.0	N/A	6			
MS 10	30.0	43.5	N/A	6			
MS 4	14.0	14.0	N/A	6			





Size:

MS

Qty:

50

Copper conducto		ctor	Aluminium conductor		MULTICORE CABLES			BLES				
Conductor wire armo			wire armoured			Conductor size						
size mm²	Number of cores		Number of cores 4			_		1.5mm ²	2.5mm ²	4mm²		
1.5		5	5	6					5 core	6	7	8
2.5		6	6	6					_			_
4		6 7	/ 8	7 8					7 core	6	7	9
6 10		8	9	9					40			
16		9	10	11		7	8	9	10 core	8	9	11
25		10	11	12		9	10	12	12 core	8	9	11
35		12	12	14		10	10	12	12 0010			
50	7	11	12	14	8	10	12	14	19 core	9	10	12
70	8	12	14	16	8	12	14	16				
95	9	14	16	18	9	14	16	18	27 core	10	12	16
120	10	16	18	20	10		16	20	_, 55.5			
150	11	16	18		12		18	20	37 core	12	14	
185	12	18			12		20		37 6016	12	14	
240	14	20			14				10		4.0	
300	16				14				48 core	14	16	