

Datasheet

RS Pro Stainless Steel Countersunk Head Machine Screws, M8 x 25mm

RS Stock No: **914-1920**



Product Details

RS Pro machine screw measuring M8 x 25 mm, is made of type 316 S16 A4 grade 18//8 stainless steel, which has higher level of corrosion resistance than A2 stainless steel. The countersunk head screw can be used at up to 300°C. The slotted drive screw is suitable for use in food, medical, chemical, construction and electronic applications.

Features and Benefits

- A4 grade 18/8 stainless steel (Type 316 S16) construction
- Higher level of corrosion resistance than A2 S/S
- Suitable for use up to 300°C
- Suitable for use in most food, medical, chemical, construction and electronic applications

Specifications:

| | |
|----------------------|------------------|
| Drive Type | Slot |
| Finish | Plain |
| Head Shape | Countersunk |
| Material | Stainless Steel |
| Length | 25 mm |
| Stainless Steel Type | 316 (A4) |
| Thread Pitch | 1.25 |
| Thread Size (Metric) | M8 |
| Head Diameter | 15.37 to 15.8 mm |
| Head Height | 4.65 mm |
| Slot Depth | 1.8 to 2.3 mm |
| Slot Width | 2 mm |
| Specification | DIN 963 |