

FEATURES

- Voltage of 220 V DC
- Green indicator light
- Needs a mounting hole of 8 mm
- LED type (light-emitting diode)
- Lamp size of 5 mm
- Lead wires
- IP67 rating so waterproof up to 1 m and dirt resistant
- Flush bezel
- Black chrome
- Current rating of 20mA
- Intensity of 8 mcd (millicandela)
- Length of 27.6 mm
- Coloured diffused epoxy lens or water clear super bright LEDs
- Operating temperature range: -40 to +85°C

RS PRO Green Indicator, 24 V dc, 8mm Mounting Hole Size, Lead Wires Termination, IP67

RS Stock No.: 700-2016



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

This RS PRO 220 V AC green indicator is designed to provide a clear signal in dark conditions. Lamps like these are often used in shipbuilding and industrial environments. Inside the pack, you'll find a durable and long-lasting LED bulb, a black chrome flush bezel, plus a fixing nut, spring washing and lead wires for attaching.

You won't have to replace this LED lamp for at least 100,000 hours, and it will consume little energy. The bulb has a 5 mm coloured epoxy lens that provides 8 mcd (millicandela) of intensity. It measures 27.6 mm long and has a 20 mA rating. Install it using an 8 mm mounting hole.

General Specifications

Light Output Colour	Green
Lamp Type	LED
Termination Type	Lead Wires
Type	Panel Mount
Bezel Style	Flush
Bezel Colour	Black Chrome
Intensity	6mcd
Type of Illumination	Fixed Light
LED Colour	Green
Viewing Angle	30°–100° (dependant on model)
Life Expectancy	100,000 hours
Applications	Industrial settings, including the food processing, transportation and marine industries

Electrical Specifications

Voltage Rating	220VAC
Current Rating	3mA

Mechanical Specifications

Mounting Hole Size	8mm
Length	28.6mm
Shape	Round
Lamp Size	5mm

Operation Environment Specifications

Temperature Rating	-40°C to 85°C
--------------------	---------------

Protection Category

IP Rating	IP67
-----------	------

Approvals

Compliance/Certifications	RoHS Compliant
---------------------------	----------------



TECHNICAL SPECIFICATIONS		
Voltage	Operating Voltage (Min to Max)	Operating Current (Typical All Types)
02 (No Resistor)	1.8 to 3.3VDC	20mA max*
6VDC	5.4 to 6.6VDC	20mA
12VDC	10.8 to 13.2VDC	20mA
24VDC	21.6 to 26.4VDC	20mA
28VDC	25.2 to 30.8VDC	20mA
110VAC	99 to 121VAC	6mA
220VAC	207 to 253VAC	3mA

Max Reverse Voltage: 5V

Viewing Angle: 30–100° (dependant on model)

Life Expectancy: 100,000 hours

Temperature Range: –40 to +85°C (operating & storage)

Torque: 20 to 25cNm

Technical drawings showing:
 - PANEL CUTOUT: A circle with diameter $\varnothing 8.00 +0.15/-0.0$.
 - M8 x 0,75 THREAD: A hexagonal nut with a diameter of 10.00 [0.394] AF and a thread length of 2.00 [0.079].

Standard LED Intensity	Prominent and Recessed	Flush	Forward Voltage
HE Red	80mcd	8mcd	2.0V
Green	60mcd	6mcd	2.2V
Yellow	50mcd	6mcd	2.1V
Blue	1600mcd	50mcd	3.3V
White	1600mcd	500mcd	3.3V
Orange	60mcd	110mcd	2.2V
Bi-color (Typical) (Red/Green)	14/30mcd	15/10mcd	2.0V/2.2V
Tri-color (Typical) (Red/Green/Yellow)	60/15/13mcd	15/10/6mcd	2.0V/2.2V/2.1V
Bi-color - The color is changed by reversing the polarity of the supply voltage.			
Tri-color - The indicator has red and green LEDs, when both connected yellow is produced.			
Super Bright LED	Prominent and Recessed	Flush	Forward Voltage
HE Red	5,000mcd	1,300mcd	2.2V
Green	10,000mcd	1,200mcd	3.3V
Yellow	4,000mcd	350mcd	2.0V
Blue	2,200mcd	280mcd	3.3V
White	2,500mcd	950mcd	3.3V
Orange	4,000mcd	500mcd	2.2V
Hyper Bright LED	Prominent and Recessed	Flush	Forward Voltage
HE Red	6,000mcd	980mcd	2.2V
Green	1,900mcd	300mcd	3.3V
Yellow	1,600mcd	250mcd	2.0V
Orange	2,400mcd	110mcd	2.2V

Luminous intensity will be reduced with lower operating current.

Note: The operating voltage must not be exceeded by more than 10% as this will result in reduced life expectancy.
 The company reserves the right to change specifications without notice.
 * Customer to supply resistor for desired operating current.
 Luminous intensity is measured at 20mA on a discrete LED unless otherwise stated.
 Luminous intensities and color shades of white LEDs may vary within a batch.
 LED characteristics are dependent upon environmental conditions. Therefore published data should be considered nominal.

Technical Drawings
FLUSH BEZEL

