

Datasheet

Stock no. 2993932

RS Pro Pneumatic Straight Threaded-to-Tube Adapter, R 1/8 Male, Push In 6 mm

**3 YEAR
WARRANTY**



Product Details

**Straight Adaptor - Male Tapered/Parallel
Threaded, Tube-to-Tube & Adaptors
Threaded Tube-to-Tube & Adaptors**

The push-on and screw collar design of these fittings makes them secure and suitable for instrumentation, vacuum and general purpose applications and they can be used with nylon or polyurethane tubing.

Operating Temperature Range -18 to +70°C

Operating Pressure of -1 to 15 bar

Each panel has integrated strength member tie positions also with the additional removable plate at the rear of the panel allows the installation of steel tape armoured cable.



Specification:

Threaded connection	R 1/8 Male
Tube connection	Push in 6mm
Tube connection – Tube size	6mm
Threaded connection – Thread size	1/8in
Threaded connection – Gender	Male
Manufacturer Series	1000
Threaded connection – Thread standard	R
Tube connection – Type	Push in
Maximum operating pressure	15 bar
Minimum operating temperature	-18°C
Maximum operating temperature	+70°C
Connector A – Thread standard	R
Tube connection A – Type	Push in
Tube connection A – Tube size	6mm
Connector A – Gender	Male
Connector A – Thread size	1/8in
Tube connection A	Push in 6mm
Connector A	R 1/8 Male
Material	Brass
Finish	Nickel Plated