Miniature Safety Limit Switch





Specifications

Rating : IEC 60947-5-1 AC-15 240V AC/3A DC-13 250V

DC/0.27A UL508 A300 250V AC/15A


Contact Resistance : 25mΩ Max.

Insulation Resistance : 100MΩ Min. (at 500V DC) Dielectric Strength : AC 1500V 50/60Hz, 1 minute Ambient Operation Temp. Range : -30°C to +70°C (with no icing)

Ambient Operating Humidity : 95% RH Max.

Degree of Protection : IP67

Diagram



Operating Characteristics

Operating Force (OF) : 6.5N (Max.) Releasing Force (RF) : 1.5N (Min.) Pretravel (PT) : 2mm Overtravel (OT) : 4mm Movement Differential (MD) : 1mm

Part Number Table

Description	Part Number
Vertical Limit Switch, Miniature Safety, w/ Front-Inserted Bending Operation Key, Screw Terminal	MC002457

Dimensions: Millimetres

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

