

ELASTEC

Duck Skimmer

Weir Skimmer for Ponds and Calm Waterways



Oil Spill Equipment | Floating Barriers | Incinerators



Duck 100

Elastec DUCK Skimmers are self-adjusting, floating weir skimmers that can be used for duckweed or water meal removal. They can also be used for oil spills.

The ELASTEC DUCK skimmer is a high capacity weir skimmer suited for inland waterways and ponds, the design incorporates a self-adjusting weir that pivots within a robust, lightweight floating frame. The suction connection is fitted with a standard Camlock coupling, to which a suitable suction pump or vacuum truck can be coupled. This skimmer automatically adjusts skimming volume according to flow created by the external pump (optional). The skimming depth can be increased with a higher flow rate. The high throughput help draw the algae over the weir, discharge from pumps can be filtered before returning water to source.



Duck 50



Weir skimmers operate by taking the surface layer of the water, material flows into the central hopper, drawn in by the water flow created by the external suction pump. Loose, floating material on the surface of the water (duckweed, algae, weeds, oil, water meal, scum) will be carried into the sump. The larger skimmer is fitted with boom connectors so that the material can be funneled to the inlet. (boom sold separately).

Available in two different sizes, depending on the size of the job and the flow rate needed to pull in material. The DUCK 50 is fitted with a 2 inch Camlock coupling, the DUCK 100 has a 4 inch. Our floating surface skimmers can skim large areas quickly and effectively. Elastec has been manufacturing skimming devices since 1990.


Contact us with your weed management issue and we can provide a solution that includes appropriate skimmer, and pump for the job.

Optional extra: Pump, hoses



Duck 100




Specifications:	
Weight:	70 lb / 31.75 kg
Dimensions:	57 x 42 x 21 inch / 146 x 106 x 43 cm
Capacity:	Variable but has been verified to function properly up to 650 gpm
Solids Handling:	Limited by pump
Suction:	4" screw on Camlock
Lifting Point:	Double handles
ASTM compliant boom connectors	



Duck 50



Specifications:	
Weight:	23 lb / 10 kg
Dimensions:	34 x 24 x 15 inch / 86 x 61 x 38 cm
Capacity:	Varies based on pump or vacuum
Suction:	2" screw on Camlock
Lifting Point:	Double handles



Pump Options

Centrifugal Pump

A self-priming centrifugal pump powered by a 15 hp 208/230V 60 Hz 3-phase electric motor. The pump is housed in a steel frame with a lifting ring and comes with an electrical disconnect with circuit breaker and 25 ft of electrical cable. Self-priming to 20 feet after initial prime. Cast iron housing with SS impeller nitrile seal and o-ring. The pump also includes a 4" ball valve for regulating the flowrate. Also available in 460V / 10hp (lower flowrate) 208-230V/460V.

Specifications:

Maximum flow:	660 gpm / 149 cu.m/hr
Maximum head:	114 feet / 34.75 m
Solids handling:	0.5 inch / 12.7 mm, 4 inch / 101.6 mm NPT suction and discharge ports fitted with 4 inch / 101.6 mm camlock adapters
Dimensions:	31 x 38 x 34 in / 0.78 x 0.97 x 0.86 m
Weight:	404 lbs



E370 Centrifugal Trash Pump

The Elastec E370 is a high volume lightweight all purpose trash pump suitable for a variety of applications - liquid transfer, flushing, dewatering etc*. This versatile pump is constructed with a Die-Cast Aluminum pump housing, with close coupled recoil start Yanmar diesel, mounted on baseplate with vibration mounts. The assembly is mounted in a stainless steel roll cage. Note: This pump is not approved for pumping flammable liquids.

Specifications:

Engine:	Diesel, Recoil Start
Capacity:	340 gpm / 77 cu.m/hr
Max Pressure:	43 psi / 2.9 bar
Max Priming Lift:	20 ft / 6 m
Discharge and Suction:	3 inch / 75 mm Camlock Couplings
Solids Handling:	1.5 inch / 38 mm
Fuel Tank Capacity:	0.76 gallon / 2.9 litre
Running Time:	4-5 hours
Dimensions:	24 x 18 x 20 inch / 0.61 x 0.46 x 0.51 m
Weight:	157 lb / 71 kg
Optional:	Suction and discharge hose, electric start, spark arrestor, wheel kit



SHOREMAX Water Pump

The ShoreMax is a lightweight portable water pump. It consists of a 3.5 HP gasoline engine (EPA compliant) driving a pump made of lightweight corrosion resistant polypropylene components.

Specifications:

Engine:	3.5 HP gasoline engine
Capacity:	200 gpm / 45 cu.m/hr
Max Pressure:	55 psi / 3.8 bar
Max Priming Lift:	20 ft / 6 m
Discharge and Suction:	2 inch / 50 mm Camlock Couplings
Solids Handling:	3/8 inch / 9.5 mm
Dimensions:	23 x 16 x 16 inch / 0.58 x 0.40 x 0.40 m
Weight:	62 lb / 28 kg



1309 West Main St.
Carmi, Illinois 62821, USA
+1 (618) 382-2525
www.elastec.com elastec@elastec.com