

## FEATURES

- Silver plated copper conductor
- PTFE Insulation to BS3G 210
- Various wire sizes and strands
- Multiple colours, including orange, blue, white and red

## RS PRO PTFE Equipment Wire 0.34 mm<sup>2</sup> CSA, Black 100m Reel

RS Stock No.: 841-7263



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

Brought to you by RS PRO, a range of wire and cables which excel within harsh environments. In areas where contamination causes an issue, such as oils, acids or excessive sunlight, these cables are specifically designed to be used within those areas. Highlighted by their copper conductor, these cables are suitable for various applications. All models are highly reliable and excellent quality.

## General Specifications

<b>Type</b>	
<b>Wire Style</b>	BS3G210
<b>American Wire Gauge</b>	22
<b>Insulation Material</b>	PTFE
<b>Resistant To</b>	Fuels, Gasoline, Hydraulic Fluid, Lubricants, Oils
<b>Core Strands</b>	19/0.15mm
<b>Conductor Material</b>	Silver Plated Copper
<b>Number of Strands</b>	19
<b>Applications</b>	Construction sites, Car engines, Aeroplanes, Petrol stations

## Electrical Specifications

<b>Voltage Rating</b>	300V
<b>Current Rating</b>	8A
<b>Conductor resistance</b>	58.6Ω /km

## Mechanical Specifications

<b>Cross Sectional Area</b>	0.336mm <sup>2</sup>
<b>Sheath Colour</b>	Black
<b>Length</b>	100m
<b>Outer Diameter</b>	1.1mm
<b>Insulation Wall Thickness</b>	0.15mm
<b>Size of Strands</b>	0.15mm
<b>Stranding</b>	19/0.15mm
<b>weight</b>	4.41kg/km


## Operation Environment Specifications

<b>Minimum Operating Temperature</b>	-75°C
<b>Maximum Operating Temperature</b>	200°C
<b>Operating Temperature Range</b>	-75°C to 200°C

## Approvals

<b>Compliance/Certifications</b>	RoHS Certificate Of Compliance
<b>Standards Met</b>	BS 3G 210:1996





8417263

8417282

8417285

8417276

8417298

8417291

8417267

8417295

8417289

8417273

8417279

**Product Range:**

<b>RS Code</b>	<b>Description</b>
8417263	PTFE A 19/0.15 black 100m
8417279	PTFE A 19/0.15 white 100m
8417267	PTFE A 19/0.15 pink 100m
8417276	PTFE A 19/0.15 red 100m
8417273	PTFE A 19/0.15 yellow 100m
8417282	PTFE A 19/0.15 blue 100m
8417285	PTFE A 19/0.15 orange 100m
8417291	PTFE A 19/0.15 violet 100m
8417289	PTFE A 19/0.15 green 100m
8417298	PTFE A 19/0.15 brown 100m
8417295	PTFE A 19/0.15 grey 100m