



Benefits

- Ideal for use in chandeliers, pendant lighting, table lamps, or floor lamps, it creates a lovely sparkling effect
- Easily match fixture color
- Up to 85% energy savings compared to incandescent bulbs

Application



Model	Item Description	W	PF	lm	lm/W	CRI	Beam Angle	Life (h)	Single Box (LxWxH)mm	Outer Box (LxWxH)mm	Packing Qty (PCS/CTN)
LC208053/dm/r9-E14	FILA C35 5.3W E14 CS 2700K DIM	5.3	0.7	470	89	92	360°	15000	40*40*110	268*220*245	60
G45F7-CL-D-4.2W-E-E27 V2 SIGV2	FILA G45 4.2W E27 CS 2700K DIM	4.2	0.8	500	119	80	360°	25000	48*48*90	322*260*205	60
A60F7-CL-D-7.2W-E-E27	SIGV1 FILA A60 7.2W E27 CS 2700K DIM	7.2	0.7	810	113	80	360°	25000	70*70*120	450*370*266	60

Application Conditions	
IP	IP20
Operating Temperature	-20~40°C
Application Temperature	25°C
Storage Environment	-25~50°C

Mechanical Properties	
Optical Material	Glass
Housing Material	Glass
Finishing Colour	Clear

Electrical Supply	
Frequency (Hz)	50/60
Voltage (V)	220-240
AC/DC	AC

Dimensional Drawing

