



Technical Specification

Material:	Virgin Closed Cell PVC (Foam)
Surface Finish:	Diamond pattern
Product Height:	9mm
Size of Safety Border:	100mm
Operating Temperature:	0°C to +60°C
Environmental Resistance:	Suitable for dry indoor environments
Typical Applications:	Production lines, assembly areas, packing stations, workbenches
Installation Method:	Loose lay
Cleaning Method:	Brush/Mop the top surface
Product Performance:	Conforms to Slip Resistance Test DIN 51130 Category R11
Flame Retardancy:	Fire Tested to DIN 54332 (B2) part of DIN 4102
Country of Origin:	China
Guarantee:	1 year guarantee when used in a dry environment
Permanent Adhesive Recommendation:	F44
Release Adhesive Recommendation:	F41
Heavy-Duty / Wet Area Adhesive Recommendation:	F74, F81, F84

Sizes (Diamond)	Black	Black/Yellow	Weight
0.6m x 0.9m	DAF010001	DAF010701	1.50 kg
0.9m x 1.5m	DAF010002	DAF010702	3.00 kg
0.9m x 18.3m	DAF010003	DAF010703	38.00 kg
0.9m x per linear metre	DAF010003C	DAF010703C	2.00 kg
1.2m x 18.3m	DAF010005	DAF010705	51.00 kg
1.2m x per linear metre	DAF010005C	DAF010705C	4.00 kg

Orthomat® Diamond

- Single layer foam anti-fatigue workplace mat with checkerplate pattern surface.
- Ideal for light to medium use in dry environments.
- Safety version available with bright yellow borders.
- Insulates against cold concrete floors.



Colour Options



Black



Safety