



Main

Range of product	PacDrive 3
Product or component type	Connector module
Accessory / separate part category	Connection accessories
Device short name	ILM

Complementary

[Us] rated supply voltage	250...700 V
[Uc] control circuit voltage	24 V DC (tolerance: - 20...25 %)
Input current	20 A
Control threshold overvoltage	860 V
Number output current	20 A
Peak output current	40 A
Physical interface	SERCOS III
Type of cooling	Natural convection
Overvoltage category	Class 3 conforming to IEC 61800-5-1
Width	44.5 mm
Height	310 mm
Depth	270 mm
Product weight	3 kg

Environment

IP degree of protection	IP20
Pollution degree	2 conforming to IEC 61800-5-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.2 cm
Package 1 Width	32.5 cm
Package 1 Length	42.5 cm
Package 1 Weight	3.15 kg
Unit Type of Package 2	S06
Number of Units in Package 2	10
Package 2 Height	75.0 cm
Package 2 Width	80.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	26.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes