

COMPRESSOR OIL TL-CO 100, 150 RCP

INDUSTRIAL GRADE

Toyo Lube is engineered for maximum protection.

Product Description

Toyo Lube Air Compressor Oil (TL-CO RCP) is specially formulated from high quality refined pure base stocks and special additives package to ensure optimum lubricating performance and maximum protection especially for the crankshaft.

TL-CO RCP series are mainly focuses in Reciprocating and Piston types of compressor.

It has excellent rust / corrosion protection and anti wear performance which allows longer service life. Besides from the above, it contains high temperature oxidation resistance and anti-foam properties to reduce deposits or sludge formation.

By the mixture of high quality additives, TL-CO RCP gives an extended drain interval comparing to the conventional type lubricants which enable compressors requiring up to 3,000+ hours operation.

Note, it is compatible with most petroleum based compressor oils including PAO and Ester and it is not compatible with glycol and silicone based compressor oils.

Benefits

- ✓ Provide extended service life
- ✓ Lower operating temperature by enhancing parts life
- ✓ Reduce energy cost and downtime
- ✓ Trouble-free operation
- ✓ Low volatility which prevent top up requirement
- ✓ Oxidation resistance for better protection

Typical Specifications

	ISO Grade	Test Method	100	150
	Flash Point °C	ASTM D-93	235	238
	Viscosity Index	ASTM D-2270	105	107
	Pour Point °C	ASTM D-97	-22	-22
	Kinematic Viscosity at			
	40°C cSt	ASTM D-445	98	152
	100°C cSt	ASTM D-445	11.5	15.8
	Rust Test	ASTM D-665B	Pass	Pass
	Colour	ASTM D-1500	<2.0	<2.0
	Corrosion and Rust Protection		Good	Good

This information is our best knowledge, true & accurate, subjected to change without prior notice due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.



MACHINES NEVER LIE

COMPRESSOR OIL TL-CO 100, 150 RCP

INDUSTRIAL GRADE

Other Information

Safety Data Sheet

Safety data sheet can be requested via website www.toyointernational.com or you may also can get them from your local agent / supplier.

SDS Number: Kindly refer to the following

Storage and Handling

This product shall be ideally stored in a cool, dry location in unopened containers. Suggested temperature between 8°C to 28°C (46°F to 82°F) unless otherwise labeled.

Stirring is recommended in order to prevent ingredients from separating.

Shelf Life

With good practicing on storage, the minimum shelf life from the batch number approx. 3 years or 36 months

Condition of the product must in the unopened original container

Available Packing Sizes

Pail	18 liter
Drum	209 liter

Part Number # TL-CO 100 RCP

8696L-0229
8696L-0934

[SDS # LP04-B04]

Part Number # TL-CO 150 RCP

Pail	18 liter
Drum	209 liter

8696L-0985
8696L-0986

[SDS # LP04-B05]

This information is our best knowledge, true & accurate, subjected to change without prior notice due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

TOYO GREASE
"MACHINES NEVER LIE"