



Main

| | |
|-------------------------------|------------------------------------|
| Range of product | Ovalis C Series |
| Product or component type | Data socket |
| Device presentation | Mechanism with fixing frame |
| Data socket type | RJ45 8 contact(s) Cat.6 <= 250 MHz |
| Type of packing | Paint cover |
| Sale per indivisible quantity | 1 |
| Condition of use | Indoor |

Complementary

| | |
|-------------------------------|---|
| Device mounting | Flush |
| Socket number | 1 |
| Organization of wire | Shielded twisted pair |
| Cable shielding type | STP |
| Product compatibility | S-one connector |
| Fixing mode | By screws |
| Colour tint | White (RAL 9003) |
| Surface finish | Matt |
| Connections - terminals | IDC |
| Number of loop terminals | 1 |
| Material | Thermoplastic ABS-UV stabilised: centre plate PBT (polybutylene terephthalate) GF30: support frame |
| Height | 71 mm |
| Width | 71 mm |
| Depth | 41.7 mm |
| Embedding depth | 25.7 mm |
| Product weight | 0.059 kg |
| Resistance to chemical agents | Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane |






Environment

| | |
|---------------------------------------|--|
| Ambient air temperature for storage | -5...50 °C |
| Ambient air temperature for operation | 5...35 °C |
| Standards | EN 50173-1 ANSI/TIA/EIA-568-B-2 TIA/EIA-568 IEC 60603-7 ANSI/TIA/EIA-568-B-2-1 IEC 60603-7-5 ISO/IEC 11801 |
| IP degree of protection | IP21 |
| IK degree of protection | IK04 |
| Environmental characteristic | Bleach Liquid soap Window-cleaning fluid Alcohol Acetone Oil UV resistant Petrol |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5.000 cm |
| Package 1 Width | 7.500 cm |
| Package 1 Length | 7.500 cm |
| Package 1 Weight | 61.000 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 5.500 cm |
| Package 2 Width | 18.000 cm |
| Package 2 Length | 36.500 cm |
| Package 2 Weight | 731.000 g |
| Unit Type of Package 3 | S04 |
| Number of Units in Package 3 | 120 |
| Package 3 Height | 30.000 cm |
| Package 3 Width | 40.000 cm |
| Package 3 Length | 60.000 cm |
| Package 3 Weight | 9.558 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation |  China RoHS Declaration |
| RoHS exemption information |  Yes |
| Environmental Disclosure |  Product Environmental Profile |