

RS Pro Datasheet

3.5mm Screwless Vertical Actuator 45° Terminal Blocks

- Interlocking modules
- 45 degree cable entry
- Kinked pins for PCB retention
- 0.75mm² (22-18AWG) solid & stranded cable
- Guided pin alignment
- Offset pinout allows greater voltage clearance
- approved

CSTBP45VD

SPECIFICATION

Rating	UL=7A/300V
Insulation resistance	500MΩ/500V
Withstand Voltage	AC2000V/1min
Contact Resistance	20mΩ (max)
Working Temperature	-40°C to 105+°C
Mouldings	UL94-V0 Flame retardant PA66
Spring Clamp	Phosphor bronze, tin plated
Recommended PCB hole size	ø1.2mm

3.5mm

TYPE NO.	POLES	LENGTH
CSTBP45VD/2	2	8.5mm
CSTBP45VD/3	3	12mm
CSTBP45VD/4	4	15.5mm
CSTBP45VD/5	5	19mm
CSTBP45VD/6	6	22.5mm
CSTBP45VD/7	7	26mm
CSTBP45VD/8	8	29.5mm
CSTBP45VD/9	9	33mm
CSTBP45VD/10	10	36.5mm
CSTBP45VD/11	11	40mm
CSTBP45VD/12	12	43.5mm

