

## FEATURES

- Quick and easy adjustment of sensor immersion length
- stainless steel for durability and corrosion resistance

# RS PRO STAINLESS STEEL COMPRESSION FITTING 1/8" BSP X 6mm (Pack of 5)

RS Stock No.: 2623243



**Pack of 5**

RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

Thermocouple installation fittings

## General Specifications

<b>General Description</b>	Compression Fitting
<b>Material</b>	Stainless Steel
<b>Style</b>	BSPP
<b>Size</b>	1/8" BSP X 6mm
<b>Pack quantity</b>	Pack of 5

## Approvals

<b>RoHS Compliant</b>	Yes
-----------------------	-----

## Ordering

<b>Pack of 1</b>	<b>Pack of 5</b>
3817356	2623243



## Similar Products

Type	Thread Size	Thread Type	Suits Probe $\emptyset$	RS order code
St/Steel	1/8"	BSP Parallel	1.0mm	<b>804-7975</b>
St/Steel	1/8"	BSP Parallel	1.5mm	<b>381-7334</b>
St/Steel	1/8"	BSP Parallel	2.0mm	<b>131-4765</b>
St/Steel	1/8"	BSP Parallel	3.0mm	<b>381-7340</b>
St/Steel	1/8"	BSP Parallel	4.0mm	<b>839-9566</b>
St/Steel	1/8"	BSP Parallel	4.5mm	<b>839-9569</b>
St/Steel	1/8"	BSP Parallel	6.0mm	<b>381-7356</b>
St/Steel	1/8"	BSP Parallel	1/4"	<b>110-4476</b>
St/Steel	1/8"	BSP Parallel	1/8"	<b>839-9557</b>
St/Steel	1/8"	BSP Parallel	3/16"	<b>839-9563</b>
St/Steel	1/4"	BSP Parallel	1.5mm	<b>178-0960</b>
St/Steel	1/4"	BSP Parallel	3.0mm	<b>381-7362</b>
St/Steel	1/4"	BSP Parallel	4.0mm	<b>178-0961</b>
St/Steel	1/4"	BSP Parallel	4.5mm	<b>839-9572</b>
St/Steel	1/4"	BSP Parallel	6.0mm	<b>381-7378</b>
St/Steel	1/4"	BSP Parallel	1/4"	<b>839-9575</b>
St/Steel	1/4"	BSP Parallel	1/8"	<b>178-0962</b>
St/Steel	1/4"	BSP Parallel	3/16"	<b>839-9547</b>
St/Steel	1/2"	BSP Parallel	3.0mm	<b>839-9579</b>
St/Steel	1/2"	BSP Parallel	4.5mm	<b>839-9588</b>
St/Steel	1/2"	BSP Parallel	6.0mm	<b>381-7407</b>
St/Steel	1/2"	BSP Parallel	8.0mm	<b>839-9581</b>

Type	Thread Type	Pitch	Suits Probe $\emptyset$	RS order code
St/Steel	M8	1mm	1.0mm	<b>136-5856</b>
St/Steel	M8	1mm	1.5mm	<b>136-5857</b>
St/Steel	M8	1mm	2.0mm	<b>136-5858</b>
St/Steel	M8	1mm	3.0mm	<b>136-5859</b>
St/Steel	M8	1mm	4.0mm	<b>178-0966</b>
St/Steel	M8	1mm	4.5mm	<b>178-0967</b>
St/Steel	M8	1mm	1/8"	<b>178-0968</b>
St/Steel	M8	1mm	3/16"	<b>178-0969</b>
St/Steel	M16	1.5mm	3.0mm	<b>839-9617</b>
St/Steel	M16	1.5mm	4.5mm	<b>178-0970</b>
St/Steel	M16	1.5mm	6.0mm	<b>839-9610</b>
St/Steel	M16	1.5mm	8.0mm	<b>839-9614</b>
St/Steel	M20	1.5mm	1.5mm	<b>178-0971</b>
St/Steel	M20	1.5mm	3.0mm	<b>136-5860</b>
St/Steel	M20	1.5mm	4.5mm	<b>136-5861</b>
St/Steel	M20	1.5mm	6.0mm	<b>136-5862</b>
St/Steel	M20	1.5mm	8.0mm	<b>178-0972</b>

Type	Thread Size	Thread Type	Suits Probe Ø	RS order code
St/Steel	1/8"	BSPT Tapered	1.0mm	<b>804-7984</b>
St/Steel	1/8"	BSPT Tapered	1.5mm	<b>286-743</b>
St/Steel	1/8"	BSPT Tapered	2.0mm	<b>131-4766</b>
St/Steel	1/8"	BSPT Tapered	3.0mm	<b>158-610</b>
St/Steel	1/8"	BSPT Tapered	4.0mm	<b>178-0963</b>
St/Steel	1/8"	BSPT Tapered	4.5mm	<b>286-759</b>
St/Steel	1/8"	BSPT Tapered	6.0mm	<b>839-9591</b>
St/Steel	1/8"	BSPT Tapered	1/4"	<b>110-4475</b>
St/Steel	1/8"	BSPT Tapered	1/8"	<b>839-9594</b>
St/Steel	1/8"	BSPT Tapered	3/16"	<b>839-9597</b>
St/Steel	1/4"	BSPT Tapered	1.5mm	<b>178-0964</b>
St/Steel	1/4"	BSPT Tapered	3.0mm	<b>381-7384</b>
St/Steel	1/4"	BSPT Tapered	4.0mm	<b>178-0965</b>
St/Steel	1/4"	BSPT Tapered	4.5mm	<b>839-9604</b>
St/Steel	1/4"	BSPT Tapered	6.0mm	<b>381-7390</b>
St/Steel	1/4"	BSPT Tapered	1/4"	<b>839-9608</b>
St/Steel	1/4"	BSPT Tapered	1/8"	<b>839-9601</b>
St/Steel	1/4"	BSPT Tapered	3/16"	<b>839-9585</b>
St/Steel	1/2"	BSPT Tapered	3.0mm	<b>839-9541</b>
St/Steel	1/2"	BSPT Tapered	4.5mm	<b>286-787</b>
St/Steel	1/2"	BSPT Tapered	6.0mm	<b>286-793</b>
St/Steel	1/2"	BSPT Tapered	8.0mm	<b>839-9550</b>

RS Components is a leading provider for Automation and Control Gear, below is a selection of best selling products:

<p style="text-align: center;"><b>rspro.com</b></p> <p style="text-align: center;"><b>Temperature. It matters</b></p>	<div style="border: 1px solid red; padding: 5px; margin-bottom: 10px;"> <p style="text-align: right;"><b>Best Sellers</b> </p> </div> <p style="text-align: center;"><b>Calibration</b></p> <p>Whether it's existing equipment or a new purchase, you need to have confidence in the accuracy of your measurements.</p> <p>That's where our calibration service can help.</p> <p>Purchase new products with confidence.</p> <p>A certificated calibrated sensor straight out of the box, ready to use.</p> <div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p style="text-align: center;"><b>RTD Detectors</b></p> <p>Wire-wound type provides greater accuracy and stability but are vulnerable to shock.</p> <p>Flat film type are resistant to shock and have quicker thermal response times.</p> <p>Various lengths and diameters available, in class A, B and 1/10th Din.</p> </div> <div style="width: 45%;"> <p><b>ANSI SYSCAL Type K Mineral Insulated Thermocouple</b> RS 181-7296</p> <p><b>IEC SYSCAL Type K Mineral Insulated Thermocouple</b> RS 181-7288</p> <p><b>IEC SYSCAL Type J Mineral Insulated Thermocouple</b> RS 181-7305</p> </div> </div> <div style="border: 1px solid red; padding: 5px;"> <p style="text-align: right;"><b>Best Sellers</b> </p> <p><b>PT1000 Thin Film Detector</b> RS 362-9907 Allied 70643582</p> <p><b>PT100 Wire Wound Detector</b> RS 611-7839 Allied 70646151</p> <p><b>PT100 Wire Wound Detector</b> RS 362-9799 Allied 70643577</p> </div>
<p style="text-align: center;"><b>Exposed Junction Thermocouples</b></p> <p>Including exposed junctions with fitted or moulded miniature plug and insulated leads, ideal for test and development applications.</p> <p>1, 2, 3, 5 &amp; 10m lengths available in IEC or ANSI colours.</p> <div style="border: 1px solid red; padding: 5px; margin-top: 10px;"> <p style="text-align: right;"><b>Best Sellers</b> </p> <p><b>ANSI Type K Exposed Junction</b> RS 814-0134 Allied 70656459</p> <p><b>ANSI Type K High Temp Exposed Junction</b> RS 131-4749 Allied 71080908</p> <p><b>IEC Type K Exposed Junction</b> RS 363-0250 Allied 70643600</p> </div>	<div style="border: 1px solid red; padding: 5px; margin-bottom: 10px;"> <p style="text-align: right;"><b>Best Sellers</b> </p> </div> <p style="text-align: center;"><b>Fabricated and Specialist Thermocouples</b></p> <p>Styles include; Magnet, Washer, Nozzle, Leaf, Bayonet &amp; Bolt thermocouple. Various lengths and calibration types available.</p> <div style="border: 1px solid red; padding: 5px;"> <p style="text-align: right;"><b>Best Sellers</b> </p> <p><b>Magnet Thermocouple</b> RS 762-1115 Allied 70651739</p> <p><b>Heavy Duty Thermocouple</b> RS 762-1128 Allied 70651743</p> <p><b>Rubber Patch Thermocouple</b> RS 290-5036 Allied 70642886</p> </div>
<p style="text-align: center;"><b>Thermocouple &amp; PRT Cable</b></p> <p>Thermocouple cables are available in IEC or ANSI colour codes. Insulation types include PFA, PTFE, PVC &amp; Fibreglass. Available spool lengths include 10, 25, 50, 100 and 200m.</p> <div style="border: 1px solid red; padding: 5px; margin-top: 10px;"> <p style="text-align: right;"><b>Best Sellers</b> </p> <p><b>IEC PVC Insulated Flat Pair</b> RS 219-4573 Allied 70641630</p> <p><b>ANSI PFA Insulated Twin Twisted</b> RS 814-0030 Allied 70656106</p> <p><b>IEC Glassfibre Insulated Flat Pair</b> RS 236-3836 Allied 70641730</p> </div>	<div style="border: 1px solid red; padding: 5px; margin-bottom: 10px;"> <p style="text-align: right;"><b>Best Sellers</b> </p> </div> <p style="text-align: center;"><b>Thermocouple Connectors</b></p> <p>Range of miniature or standard thermocouple connectors. Available in thermocouple types K, J, T, E, N, RS, B, and copper. IEC, ANSI &amp; JIS colour codes available.</p> <div style="border: 1px solid red; padding: 5px;"> <p style="text-align: right;"><b>Best Sellers</b> </p> <p><b>IEC Thermocouple Plug</b> RS 455-9764 Allied 70644391</p> <p><b>ANSI Thermocouple Socket</b> RS 769-1127 Allied 70652125</p> <p><b>IEC Thermocouple PCB Socket</b> RS 381-7570 Allied 70643749</p> </div>

RS Components is a leading provider for Automation and Control Gear, below is a selection of best selling products:

 <p><b>Mineral Insulated Thermocouples</b></p> <p>Available in various calibration types with a variety of terminations. These include; Thermocouple plugs, Terminal heads and Thermocouple cable</p>	<p><b>Best Sellers</b> </p> <p><b>IEC Thermocouple with PTFE Cable</b> RS 397-1236 Allied 70643843</p> <p><b>IEC Thermocouple with Mini Plug</b> RS 397-1488 Allied 70643863</p> <p><b>ANSI Thermocouple with PFA Cable</b> RS 847-1019 Allied 70658112</p>	 <p><b>NEW PRODUCTS</b></p> <p>RS PRO, the own brand of RS Components, offers an unbeatable range of products across all industries with quality you can trust.</p> <p>New products are constantly added to improve the offering of our product range.</p>	<p><b>NEW PRODUCTS</b> </p> <p><b>Brake Pad Temp Sensor</b> RS 200-0601 Allied 72173869</p> <p><b>RTD Temp Sensor Hirschmann Style</b> RS 200-0594 Allied 72173862</p> <p><b>Washer Thermocouple</b> RS 200-0616 Allied 72173882</p>
 <p><b>Sensors with Industrial Terminal Heads</b></p> <p>Industrial sensors housed in a stainless steel sheath and terminal head protection to IP67. Available as a thermocouple or Pt100.</p>	<p><b>Best Sellers</b> </p> <p><b>Type K 300mm Long</b> RS 787-7829 Allied 70653306</p> <p><b>Type K 200mm Long</b> RS 787-7816 Allied 70653303</p> <p><b>Type K 100mm Long</b> RS 787-7804 Allied 70653235</p>	<p><a href="http://www.rspro.com">www.rspro.com</a></p>  <p><a href="http://www.alliedelec.com">www.alliedelec.com</a></p>	
 <p><b>L60 Fine Wire Thermocouple Welder</b></p> <p>The Thermocouple Welder is a compact, simple-to-use instrument designed for thermocouple and fine wire welding. Supplied with foot switch, spare electrodes, pliers &amp; safety glasses, impact clip and pen plate.</p>	<p><b>Best Sellers</b> </p> <p><b>L60 Fine Wire Thermocouple Welder</b> RS 363-0351 Allied 70825788</p> 		