

特点:

- 结构紧凑，造型美观。
- 操作简单、工作效率高。
- 广泛应用于建筑、设备安装、石油化工及大中型工矿企业的施工、安装和维修。

CHARACTERS:

- Compact configuration, handsome sculpt.
- Easy operation, high efficiency.
- Widely use in the construction of building.



Z1T-50/Z3T-50



Z1T-80/Z3T-80



Z1T-100/Z3T-100



T1X-100/T3X-100

| 型号Model | Z1T-50/Z3T-50 | Z1T-80/Z3T-80 | Z1T-100/Z3T-100 | T1X-100/T3X-100 |
|-----------------------|---------------|---------------|-----------------|-----------------|
| 加工范围 Capacity | 1/2"-2" | 1/2"-3" | 1/2"-4" | 1/2"-4" |
| 主轴转速 Speeds | 28rpm | 11,23rpm | 8.5,24rpm | 10,18rpm |
| 电动机 Motor | 750W | 750W | 750W | 750W |
| 额定电压 Power supply | 220/380V | 220/380V | 220/380V | 220/380V |
| 毛重/净重 G.W./N.W. | 68/60kg | 130/110kg | 195/182kg | 150/140kg |
| 包装尺寸 Ship measurement | 73×51×51cm | 86×61×63cm | 101×69×68cm | 95×54×49cm |