



Main

Product or component type	Power socket-outlet
Socket additional information	Shuttered
Load type	Resistive
Cover frame colour tint	Silver bronze

Complementary

Device mounting	Flush Surface
Rated current	16 A at 250 V AC 50 Hz
Number of gangs	1 gang
Material	Polycarbonate base Brass metal parts Nylon + GF shutter Polycarbonate cover Steel metal parts
Connections - terminals	Brass rod terminals
Width	87 mm
Height	87 mm
Depth	29 mm

Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
Operating altitude	2000 m
Standards	IEC 60884-1
Standards	IEC 60884-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.5 cm
Package 1 Width	15 cm
Package 1 Length	2.375 cm
Package 1 Weight	121.875 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm

Package 2 Weight	975 g
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	21 cm
Package 3 Width	32.5 cm
Package 3 Length	50 cm
Package 3 Weight	9750 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Circularity Profile	End Of Life Information