


## **FEATURES**

- Durable Mineral Insulated type thermocouples to suit a wide range of temperature measurement. Various probe types, lengths, and diameters available
- JIS Thermocouple
- 1 Metre PFA Insulated Flat Pair Cable and Tails 7/0.2mm
- Japanese Industrial Standards (JIS) are the standards used for industrial activities in Japan

# JIS Mineral Insulated Thermocouples 1.0mm x 150mm with 1 Metre PFA Insulated Flat Pair Cable and Tails

RS Stock No.: 2394607



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



#### **Product Description**

Durable Mineral Insulated type thermocouples to suit a wide range of temperature measurement. Various probe types, lengths, and diameters available.

### **General Specifications**

Thermocouple Type	Туре К		
Temperature Measurement Range	+1100°C (+750°C for 1mm)		
Construction	Flexible mineral insulated probe with stainless steel sheath, plain pot seal & 1 metre extension cable		
Standards Met	JIS (Japanese Industrial Standards)		

#### Mechanical Specifications

Probe Diameter Probe Length	1.0mm 150mm
Pot	Plain (200°C)
Element/hot junction	Single element, junction insulated from sheath (offers protection against spurious electrical signals)
Probe Body Material	Stainless steel 310 sheath
Termination Type	1 metre 7/0.2mm PFA Teflon® insulated flat pair cable with tails

#### Approvals

<b>Compliance/Certifications</b>	RoHS Compliant

### Similar Products Range

Diameter	150mm Length	250mm Length	500mm Length
1.0mm	2394607	2394610	2394608
1.5mm	2394609	2394612	2394613
3.0mm	2394611	2394614	2394615
6.0mm	2394617	2394618	2394619



RS Components is a leading provider for Automation and Control Gear, below is a selection of best selling products:





RS Components is a leading provider for Automation and Control Gear, below is a selection of best selling products:

