


FEATURES

- Effective restrain surge
- Low power loss under the stable state
- Over-current wide control range and fast response
- Thermal and electrical characteristics with high stability
- Wide range of electrical specifications

RS PRO Protection NTC Thermistor 5Ω , 13 (Dia.) x 6mm

RS Stock No.: 516-7833



Protection NTC Thermistor



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

A range of PCB mounting metal oxide ceramic inrush current suppressors which when cold at initial switch on, present a high series resistance and limit current flow

As the devices warm the resistance progressively reduces to allow normal current to flow

The device quickly cools and returns to high resistance when the power is switched off

Suitable for switched mode power supplies, small electric motors, filament lamps, transformers etc

General Specifications

Model Number	N13SP005M	
Style	Disc Type Thermistor (Negative Temperature Coefficient)	

Mechanical Specifications

Material of coating	Silicone
Colour of coating	Green
Material of lead wire	Cu, Fe, Sn

Electrical Specifications

Zero Power Resistance at 25°C	5 Ω		
Maximum Steady State Current at 25°C	5 A		
Residual Resistance at 25°C Imax (R _{Imax})	0.150 Ω		
Typical value	Thermal Time Constant	93s	
Typical value	Thermal Dissipation Constant	17mW/°C	
Recommend Capacitance 240Vac	430 μF		
Maximum Steady Power	3.0 W		
Operating Temperature Range	-40~+200 °C		

Protection NTC Thermistor



TUV Yes

Protection Category

IP Protection N/A

Additional Information

EAN	N/A
Custom Tariff Number	N/A

Classification

eCl@ss (Version)	N/A
UNSPSC (Version)	N/A

Approvals


Declarations	N/A
Hazardous Area Certification	N/A
Standards Met	IEC 60068

Similar Products


Stock No.	Brand	Product Name	Attribute 1	Attribute 2	Attribute 3
516-7811	RS PRO	Thermistor 8Ω, 13 (Dia.) x 6mm			



Resistance- Temperature Characteristic Curves



V-I Characteristic Curves



Protection NTC Thermistor



Connection Diagrams / Assembly Diagrams / Illustrations / Accessories