

GS1JD3

Switch disconnecter fuse, TeSys GS, 3P, 3NO, 100A, 9W, fuse type NFC, size 22x58mm



Main

Range	TeSys
Product name	TeSys GS
Device short name	GS1 J
Product or component type	Switch-disconnector-fuse
Device application	Protection
Poles description	3P
Protected poles description	3t
Contacts type and composition	3 NO
[I _{th}] conventional free air thermal current	100 A (at 40 °C)
[I _e] rated operational current	100 A at 440 V 2 poles in series per phase DC-23A 100 A at 440 V 2 poles in series per phase DC-23B 100 A at 690 V with terminal cover AC-23A 100 A at 690 V with terminal cover AC-23B 100 A at 400 V AC-23A 100 A at 400 V AC-23B 100 A at 500 V AC-23A 100 A at 500 V AC-23B
Fuse type	NFC
Fuse size	22 x 58 mm
Network type	AC DC
Network frequency	50/60 Hz

Complementary

Type of operating handle	Direct right side
Mounting support	Plate
[U _i] rated insulation voltage	750 V AC 50/60 Hz
[U _{imp}] rated impulse withstand voltage	8 kV
Rated operational power in W	55 kW at 400 V 75 kW at 500 V 90 kW at 690 V
Breaking capacity	9 W
Making capacity	1000 A at 400 V AC-23B
Breaking capacity	800 A at 400 V (AC-23B)
Short-circuit withstand	20 kA
Mechanical durability	10000 cycles
Electrical durability	1500 Cycles AC-23A 1500 Cycles AC-23B 300 Cycles DC-23A 300 cycles DC-23B
Connections - terminals	Power circuit: bars Power circuit: lugs-ring terminals 25...95 mm ² flexible
[I _{cm}] rated short-circuit making capacity	100 kA at 400 V with protection by gG fuses
Tightening torque	Power circuit: 12 N.m - on bars Power circuit: 12 N.m - on lugs-ring terminals

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Standards	IEC 60947-3
Product certifications	CE
Protective treatment	TH
IP degree of protection	IP20 conforming to IEC 60529 (with terminal cover)
Ambient air temperature for operation	-20...70 °C
Ambient air temperature for storage	-40...80 °C
Fire resistance	850 °C fuse cover conforming to IEC 60695-2-1 960 °C body conforming to IEC 60695-2-1
Height	162 mm
Width	150 mm
Depth	116 mm
Net weight	1.5 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.5 cm
Package 1 Width	21.0 cm
Package 1 Length	22.5 cm
Package 1 Weight	1.737 kg
Unit Type of Package 2	S06
Number of Units in Package 2	27
Package 2 Height	75.0 cm
Package 2 Width	60.0 cm
Package 2 Length	80.0 cm
Package 2 Weight	59.899 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------