

## Features

- Slow blow fuse
- Base and cap in black thermoplastic
- Round pins in tin plated copper
- Vibration MIL-STD-202G
- Salt spray MIL-STD-202G
- Insulation resistance MIL-STD-202G
- Resistance to solder heat MIL-STD-202G
- Thermal shock MIL-STD-202G

## RS PRO Radial Non-Resettable Wire Ended Fuse

RS Stock No.: 767-5052



RS PRO Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

The RS PRO radial non-resettable fuse withstands currents up to 3.15 A and voltages up to 250 V. It has thermoplastic body for added durability. This slow blow fuse forms a convenient and reliable solution to a vast array of application requirements.

## General Specifications

Fuse Type	Time Lag
Lead Orientation	Radial
Body Material	Thermoplastic
Wire Diameter	0.62 mm
Wire Length	22 mm
Wire Pitch	5.08 mm

## Electrical Specifications

Breaking Capacity (at Maximum Voltage Rating)	35 A at 250 V ac
Current Rating	3.15 A
Voltage Rating	250 V

## Mechanical Specifications

Body Height	7.7 mm
Body Length	8.35 mm
Body Width	4.3 mm

## Operation Environment Specifications

Maximum Operating Temperature	+125°C
Minimum Operating Temperature	-55°C
Nominal Resistance	0.0188 Ω

# Non Resettable Fuses

## Approvals

Standards Met	SEMKO, VDE, TUV, CSA, UL, CCC, KTL, PSE, RoHS
---------------	---