



## 1965 MityLite™

### YOUR WORLDWIDE PASSPORT THROUGH HAZARDOUS LOCATIONS

While working in hazardous locations, remember a flashlight can be an ignition source. When you need the latest and brightest LED technology in a compact form factor, choose the new **MityLite™ 1965 LED** from Pelican. Small enough to fit in your shirt pocket, yet bright enough to illuminate your work area.

Long lasting, energy efficient, bright LEDs, along with a compact package make the new **MityLite™ 1965 LED** the safety approved light for the job.

- Compact and Lightweight
- IPX7 Waterproof
- Twist on/off activation
- 2 AAA Batteries




## DIMENSIONS

|               |                 |
|---------------|-----------------|
| <b>Length</b> | 5.48" (13.9 cm) |
|---------------|-----------------|

## MATERIALS

|                                |                          |
|--------------------------------|--------------------------|
| <b>Body</b>                    | EXL                      |
| <b>O-Ring</b>                  | EPDM                     |
| <b>Lens</b>                    | Clear Polycarbonate (PC) |
| <b>Shroud</b>                  | EXL                      |
| <b>Contact Spring Retainer</b> | Phosphore Bronze         |

## COLORS

|   |  |
|---|--|
|  Black |  High Visibility Yellow |
|---|--|

## LIGHT SPECS

|                  |     |
|------------------|-----|
| <b>Lamp Type</b> | LED |
|------------------|-----|

## POWER

|                           |          |
|---------------------------|----------|
| <b>Battery Size</b>       | AAA      |
| <b>Battery Type</b>       | Alkaline |
| <b>Battery Quantity</b>   | 2        |
| <b>Batteries Included</b> | yes      |
| <b>Volts</b>              | 3.0v     |

## WEIGHT

|                                 |                |
|---------------------------------|----------------|
| <b>Weight With Batteries</b>    | 1.9 oz (54 gr) |
| <b>Weight Without Batteries</b> | 1.1 oz (31 gr) |

## SWITCH

|                    |          |
|--------------------|----------|
| <b>Switch Type</b> | Rotary   |
| <b>Light Modes</b> | On / Off |

# CERTIFICATIONS







---

Class I, Division 1  
Class II, Division 1  
Class III, Division 1

# OTHER

---

**Minimum Pack** 12  
**Package Code** C

| FL1 STANDARD  | HIGH         |
|---|--------------|
|    | 87<br>LUMENS |
|    | 2h 30mins    |
|   | 41m          |
|  | 429cd        |
|  | 2m           |
|  | IPX7         |

---

## Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

Document created on 04-04-19