



### Main

Range	Actassi
Product or component type	Power distribution rail
Device application	Multi-purpose
Outlet standard description	Pin earth
Accessory / separate part category	Current distribution accessory
Outlet poles configuration	2P + E with shutters
Quantity per set	Set of 1
Colour	Aluminium

### Complementary

Device composition	1 power rail Fixing elements
Ground lug position	35° ground lug
Socket number	9
[In] rated current	16 A
[Ue] rated operational voltage	230 V AC
Mounting support	Upright 19" rack
Fixing mode	Direct fixing By brackets
Material	Polyamide 6 with 30 % fibre glass
Surface finish	Anodized
Electrical connection	3 m power cord 3 x 1.5 mm <sup>2</sup> H05VV-F3G1.5
Number of rack unit	1U
Width	482.60 mm
Depth	44 mm

### Environment

Fire resistance	850 °C
Quality labels	UTE
Standards	IEC 60884 NBN C 61-112-1 NFC 61-314

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.0 cm
Package 1 Width	10.0 cm
Package 1 Length	50.0 cm
Package 1 Weight	861.0 g

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>