PVC Blanking Grommet PV Series

pro-**Power**



Features:

- · A range of black PVC blanking grommets for all general industrial installation type uses
- Maximum panel thickness : 1.6 mm

Hardness ±5 (Shore A) 61 Softness ±5 (BSS) 70

Operating temperature

: -35°C to +70°C

Specification Table:

Panel Hole Diameter (a)	(b)	(d)	(e)	Outside Diameter (f)	(g)	Packaging	Part Number
15.9 (0.63)	1.6 (0.06)	4 (0.16)	2.4 (0.09)	22.2 (0.87)	19 (0.75)	100 per pack	PV507 GROMMET PK 100
20 (0.79)				25.4 (1)	22.2 (0.87)		PV510M GROMMET PK 100
25.4 (1)		4.8 (0.19)		31.8 (1.25)	28.6 (1.13)		PV516A GROMMET PK 100

General tolerance : ±0.25 mm

Dimensions : Millimetres (Inches)

Part Number Table

Description	Part Number		
PVC Blanking Grommet, 15.9mm, PK100	PV507 GROMMET PK 100		
PVC Blanking Grommet, 25.4mm, PK100	PV510M GROMMET PK 100		
PVC Blanking Grommet, 31.8mm, PK100	PV516A GROMMET PK 100		

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

