

# **FEATURES**

- Operating temperature range is from - 60 °C to + 300 °C
- RoHS and REACH compliant
- Silicon free

# RS PRO STRAIGHT MALE ADAPTOR (TAPER)

RS Stock No.: 2312604



RS PROfessionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



### **Product Description**

The RS PRO straight male adaptor (taper) is made up of brass.

The working pressures and working temperatures depend on which type of tube is used, for this reason, the values must be determined in accordance with the tube's features.

Hereunder, we specify the values of the maximum pressure advised for the fittings at a temperature of 20° C connected with copper tube, which has a thickness of 1 mm.

Here the tube size is 18 and corresponding maximum pressure advised is 69.3 bar.

#### **General Specifications**

Fitting Type	Adapter
Material	Brass
Fitting Direction	Straight
Application	Compressed Air, Pneumatic Automation, Industrial water circuits, Inert Gases, Fluids, Steam Vacuum

#### **Mechanical Specifications**

Pipe Fitting Connection Type	Threaded		
Connection 1	M14 Metric Female		
Connection Gender 1	Female		
Thread Size 1	M14		
Thread Standard 1	Metric		
Connection 2	1/2 in BSP Male		
Connection Gender 2	Male		
Thread Size 2	1/2 in		
Thread Standard 2	BSP		
Length	43.5mm		
Wrench Size	24mm		




# **Operation Environment Specifications**

Temperature	Min.	Max.
	- 60°C	+300°C

## **Similar Products**

Parameters	2312779	2312778	
Brand	RS PRO	RS PRO	
Pipe Fitting Connection Type	Threaded	Threaded	
Connection 1	1/4 in BSPT Male	1/2 in BSPT Male	
Connection Gender 1	Male	Male	
Thread Size 1	1/4 in	1/2 in	
Thread Standard 1	BSPT	BSPT	
Connection 2	1/4 in NPTF	1/2 in NPT Male	
Connection Gender 2	Male	Male	
Thread Size 2	1/4 in	1/2 in	
Thread Standard 2	NPTF	NPTF	
Length	29mm	36.5mm	
Wrench Size	14mm	22mm	



Tube	Α	L	СН	Pack.
18	1/2	43.5	24	10