N Plug to 7/16 Jack Adapter Multicomp PRO

RoHS Compliant



Specifications

Frequency Range : DC-7.5 GHz

Nominal Impedance : 50Ω

Working Voltage : 1000 Volts Max.
Proof Voltage : 1500 Volts

Vswr : 1.3

Bodies : Brass per JIS-C3604


Centre Contact : Beryllium copper per ASTM B196 UNS C17300

BRASS PER JIS-C3604

Insulation : PTFE Per ASTM D1457 and ASTM D1710

Operating Temperature Range : -65°C to +165°C

Diagram



| No. | Description | Material | Finish | Qty. |
|-----|------------------|----------------------|--------------------|------|
| 1 | Shell | Brass | Silver 70µ" Min. | |
| 2 | Gasket | Silicone | Red | |
| 3 | Washer | Brass Silver 70µ" Mi | None | 1 |
| 4 | Centre Contact I | | Silver 70u" Min | |
| 5 | Body I | | Silver 70µ Iviiri. | |
| 6 | Insulation | PTFE | None | |
| 7 | Body II | Brass | Silver 70µ" Min. | |
| 8 | Centre Contact I | Beryllium Copper | | |

Part Number Table

| Description | Part Number | |
|-----------------------------|-------------------------|--|
| N Plug to 7/16 Jack Adapter | MP-R38-018-00-004741000 | |

Dimensions : Millimetres (Inches)

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro



Page <1> 27/09/21 V1.0

Heading



N Plug to 7/16 Jack Adapter multicomp PRO

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

