

Datasheet

RS Pro Non-Fused Terminal Block, 12 Way/Pole, Screw Terminals, 4 mm² Panel Mount, PA, 400 V

RS Stock No: **868-0815**



Product Details

RS Pro non-fused terminal block in natural colour, has nylon polyamide housing with 25% fibreglass UL 94 V-0. This block with 12 ways, has nickel plated brass contact. This terminal block with 4-mm² wire, features screw termination. The panel mount block has a voltage rating of 400 V.

Features and Benefits

- Maximum continuous temperature of 140°C and for short periods of 200°C
- Test current of 41 A
- galvanised steel M3.5 x 7 screws
- Meets UL 94 V-0, EN 60335-1: 2002 + A2: 2006 (S.C. 30.2.3), IEC/EN 60695-2-11 and CE standards

**Specifications:**

Contact Material	Brass
Contact Plating	Nickel
Enclosed	No
Material	Polyamide, Nylon/Fibreglass
Maximum Operating Temperature	+125°C
Mounting Type	Panel Mount
Number of Ways	12
Pitch	12 mm
Termination Method	Screw
Voltage Rating	400 V
Wire Size	4 mm ²
Colour	Natural
Screw Size	M3.5 x 7
Standards Met	RoHS, UL 94V-0, EN 60335-1:2002 + A2:2006 (S.C. 30.2.3), IEC/EN 60695-2-11, CE