

FEATURES

- Shrink ratio: 3:1
- Semi-rigid, abrasion resistant
- Waterproof, moisture and UV resistant
- meet very strict requirements of mechanical performance
- Excellent electrical insulation properties
- Compliance with RoHS and REACH environmental regulations
- Continuous operating temperature: -55°C~110°C
- Minimum shrink temperature: 80°C
- Full recovery temperature: Above 120°C
-

RS PRO Heat Shrink Tubing

Heavy Wall Adhesive Lined Heat Shrink Tubing



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description
ATTRIBUTE 1

It has a thicker wall thickness for better outer protection. With excellent abrasion and corrosion resistance, it is suitable for the insulation protection of cables and terminals and is widely used in communications, power cables and chemical pipelines.

General Specifications

Part Number	As supplied (mm)	After recovered (mm)		Standard Length (Meter / EA)
	I.D.(min)	I.D.(max)	W.T(min)	
2269084	22	6	2.7	1.22 meter/EA
2269083	13	4	2.5	1.22 meter/EA
2269085	40	12	4.1	1.22 meter/EA
2269086	95	30	4.3	1.22 meter/EA
2269088	180	50	4.3	1.22 meter/EA

Technical Data

Property	Test Method	Typical Value
Tensile strength	ASTM D638	≥12MPa
Elongation at break	ASTM D638	≥350%
Elongation at break after aging	ASTM D638 (150°C/168 hrs)	≥300%
Dielectric strength	ASTM D2671	≥10kV/mm
Volume resistivity	ASTM D876	≥10 ¹² Ω·cm

Additional Information

EAN	8000126233360
Custom Tariff Number	39173900

Approvals

Declarations	RoHS REACH MFR Declaration of Conformity
Hazardous Area Certification	ATEX / IECEx
Standards Met	