

FEATURES

- Excellent microprocessor control guarantees high reliability;
- A wide range of applicable voltage;
- Boost and buck AVR for voltage stabilization;
- Auto restart while AC is recovering;
- Off-mode charging,,Cold start function;
- Simulation sine wave;

RS PRO Online Rack Mount/ Standalone UPS - 2.4kW

RS Stock No.: 2355107



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

RS PRO Online Rack Mount/Standalone UPS - 2.4kW

General Specifications

MODEL	2355107
CAPACITY	360W

Electrical Specifications

INPUT	
Voltage	220Vac / 230Vac
Voltage Range	140 - 300 Vac
Frequency Range	>40 Hz (auto sensing)
OUTPUT	
Voltage Regulation (Batt. Mode)	220Vac / 230Vac/240Vac±10%
Frequency Range (Batt. Mode)	50Hz±1Hz or 60Hz±1Hz (auto sensing)
Transfer Time	Typical 4-8ms, 13ms max
Waveform (Batt. Mode)	Simulated Sine Wave
BATTERY	
Battery Voltage	12V
Battery number	7Ah*1
Maximum Charge Current	1.0 A
INDICATORS	
AC Mode	Green LED lighting
Battery Mode	Orange LED flash
Plug Type	UK Plug Type G

Uninterruptible Power Supplies

Fault	<i>Red LED lighting</i>
Protection	
Full Protection	<i>Short circuit, Overload , Overcharge and overdischarge protection</i>
ALARM	
Battery mode	<i>Sounding every 10 seconds</i>
Low Battery	<i>Sounding every second</i>
Overload	<i>Sounding every 0.5 seconds</i>
Fault	<i>Continuously sounding</i>
Physical	
Dimension,D*W*H (mm)	<i>306*86*140</i>
Net Weight(kgs)	<i>4.7</i>
Operating Environment	
Humidity	<i>0-90 % RH @ 0- 40 ° C(non-condensing)</i>